

ISO 11898-1:2003-12 (E)

Road vehicles - Controller area network (CAN) - Part 1: Data link layer and physical signalling

Contents		Page
Foreword		v
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Terms and definitions	2
5	Symbols and abbreviated terms	3
6	Basic concepts of CAN	5
6.1	CAN properties	5
6.2	Frames	5
6.3	Bus access method	5
6.4	Information routing	5
6.5	System flexibility	5
6.6	Data consistency	5
6.7	Remote data request	6
6.8	Error detection	6
6.9	Error signalling and recovery time	6
6.10	ACK	6
6.11	Automatic retransmission	6
6.12	Fault confinement	6
6.13	Error-active	6
6.14	Error-passive	6
6.15	Bus-off	7
7	Layered architecture of CAN	7
7.1	Reference to OSI model	7
7.2	Protocol specification	8
7.3	Format description of services	9
7.4	LLC interface	9
8	Description of LLC sublayer	10
8.1	General	10
8.2	Services of LLC sublayer	10
8.3	Functions of LLC sublayer	14
8.4	Structure of LLC frames	14
8.5	Limited LLC frames	16
9	Interface between LLC and MAC	16
9.1	Services	16
9.2	TTC option	16
10	Description of MAC sublayer	17
10.1	General	17
10.2	Services of MAC sublayer	17
10.3	Functional model of MAC sublayer architecture	21
10.4	Structure of MAC frames	24

10.5	Frame coding	29
10.6	Order of bit transmission	30
10.7	Frame validation	30
10.8	Medium access method	30
10.9	Error detection	32
10.10	Error signalling	33
10.11	Overload signalling	33
10.12	Bus monitoring	33
11	LLC and MAC sublayer conformance	33
12	Physical layer	33
12.1	General	33
12.2	Functional model	33
12.3	Services of PL	34
12.4	PLS sublayer specification	35
12.5	PLS-PMA interface specification	39
13	Description of supervisor	39
13.1	Fault confinement	39
13.2	Bus failure management	44
	Bibliography	45