

# ISO 4138:2004-09 (E)

## Passenger cars - Steady-state circular driving behaviour - Open-loop test methods

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Principle</b> .....	<b>1</b>
<b>4.1</b>	<b>Test methods</b> .....	<b>1</b>
<b>4.2</b>	<b>Equivalence of test methods</b> .....	<b>2</b>
<b>5</b>	<b>Variables</b> .....	<b>2</b>
<b>5.1</b>	<b>Reference system</b> .....	<b>2</b>
<b>5.2</b>	<b>Measurement</b> .....	<b>2</b>
<b>6</b>	<b>Measuring equipment</b> .....	<b>3</b>
<b>6.1</b>	<b>Description</b> .....	<b>3</b>
<b>6.2</b>	<b>Transducer installation</b> .....	<b>3</b>
<b>6.3</b>	<b>Data processing</b> .....	<b>3</b>
<b>7</b>	<b>Test conditions</b> .....	<b>3</b>
<b>8</b>	<b>Test procedure</b> .....	<b>3</b>
<b>8.1</b>	<b>Warm-up</b> .....	<b>3</b>
<b>8.2</b>	<b>Initial driving condition</b> .....	<b>4</b>
<b>8.3</b>	<b>General test description</b> .....	<b>4</b>
<b>8.4</b>	<b>Method 1 -- Constant-radius</b> .....	<b>4</b>
<b>8.5</b>	<b>Method 2 -- Constant steering-wheel angle</b> .....	<b>5</b>
<b>8.6</b>	<b>Method 3 -- Constant-speed</b> .....	<b>6</b>
<b>9</b>	<b>Data analysis</b> .....	<b>6</b>
<b>9.1</b>	<b>General</b> .....	<b>6</b>
<b>9.2</b>	<b>Lateral acceleration</b> .....	<b>7</b>
<b>9.3</b>	<b>Path radius</b> .....	<b>7</b>
<b>10</b>	<b>Data evaluation and presentation of results</b> .....	<b>7</b>
<b>10.1</b>	<b>General</b> .....	<b>7</b>
<b>10.2</b>	<b>Plotted results (see Annex A)</b> .....	<b>7</b>
<b>10.3</b>	<b>Evaluation of characteristic values</b> .....	<b>8</b>
<b>Annex A (normative) Presentation of results</b> .....		<b>12</b>
<b>Annex B (normative) Determination of overall (static) steering ratio</b> .....		<b>17</b>
<b>Annex C (informative) General information -- Theoretical basis for the test methods</b> .....		<b>18</b>
<b>Bibliography</b> .....		<b>19</b>