ISO 7308:1987-12 (E)

Road vehicles; Petroleum-based brake-fluid for stored-energy hydraulic brakes

Contents

Page

1 Scope 1

2 Field of application 1

3 References 1

4 Definition 1

5 Materials 1

6 Requirements 1
6.1 Boiling point 1
6.2 Viscosity 2
6.3 Water content 2
6.4 Fluidity and appearance at low temperatures 2
6.5 Hygroscopicity 2
6.6 Foaming 2
6.7 Connpatibility 2
6.8 Effect on rubber 2
6.9 Performance under simulated Service 2
6.10 Corrosion 3
6.11 Shear stability 3
6.12 Anti-wear stability 3

7 Test methods 3
7.1 Boiling point 3
7.2 Viscosity 3
7.3 Water content 3
7.4 Fluidity and appearance at low temperatures 3
7.5 Hygroscopicity 3
7.6 Foaming 4
7.7 Compatibility 4
7.8 Effect on rubber 4
7.9 Performance under simulated Service 5
7.10 Corrosion 8
7.11 Shear stability 10
7.12 Anti-wear properties 10

Annexes A Acrylonitrile-butadiene rubber (NBR) brake cups to test brake-fluid complying with ISO 7308 11

B Hiding power Chart 15

C Mixed formulae and basic mechanical characteristics of the rubber used for tests simulating the effect on rubber 16

D Assembly of metal strips for corrosion test in brake-fluids used for full-power hydraulic systems with pump 17

E Chemical composition of metal pieces for corrosion test 19

F Specifications of balls used in tests carried out with the four-ball machine, for anti-wear properties 20