

ISO 15830-3:2005-12 (E)

Road vehicles - Design and performance specifications for the WorldSID 50th percentile male side-impact dummy - Part 3: Electronic subsystems

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Electrical subsystems requirements	2
4.1	Permissible sensors	2
4.1.1	General	2
4.1.2	Locations and specifications	2
4.1.3	Sensor specifications and mass	3
4.2	Permissible internal data acquisition system (DAS)	7
4.2.1	General	7
4.2.2	DAS characteristics	7
4.2.3	DAS mass and mass distribution	8
5	Methods	8
5.1	Calculation of IR-TRACC distances from the IR-TRACC voltage outputs	8
	Annex A (normative) Load cell characteristics	10
A.1	Load cell capacities	10
A.2	Load cell sign conventions	10
	Annex B (informative) Conventions for exemplar permissible load cells and angular displacement sensors	15
B.1	Overview	15
B.2	Repeatability and reproducibility	15
B.3	Durability	15
B.4	Sensitivity	15
B.5	Handling	15
B.6	Calibration	17
B.7	Load cell connector pin codes	17
B.8	Universal neck load cell (W50-71000)	19
B.9	Sacro-iliac load cell (W50-71130)	19
B.10	Lumbar load cell (W50-71120)	20
B.11	Pubic symphysis load cell (W50-71051)	20
B.12	Femoral neck load cell (W50-71080)	20
B.13	Universal leg load cell (W50-71010)	20
B.14	Shoulder load cell (W50-71090)	20
B.15	Universal arm load cell (W50-71070)	20
B.16	Elbow load cell (W50-71060)	20
B.17	Knee contact load cell (W50-71020)	21
	Annex C (informative) Conventions for exemplar permissible accelerometers	22

C.1	Overview	22
C.2	Linear accelerometer connector pin codes	22
C.3	Rotational accelerometer connector pin codes	22
Annex D (informative) Information regarding sensor output polarities		24
D.1	Overview	24
D.2	Sensor output polarity diagrams	24
Figures	Figure A.1 -- Universal neck load cell	11
	Figure A.2 -- Sacro-iliac load cell	11
	Figure A.3 -- Sacro-iliac load cell, right side, top, and left side views	11
	Figure A.4 -- Lumbar load cell	12
	Figure A.5 -- Pubic symphysis load cell	12
	Figure A.6 -- Femoral neck load cell	12
	Figure A.7 -- Universal leg load cell	13
	Figure A.8 -- Shoulder load cell	13
	Figure A.9 -- Universal arm load cell	13
	Figure A.10 -- Elbow load cell	14
	Figure A.11 -- Knee contact load cell	14
	Figure B.1 -- Robert A. Denton WorldSID instrumentation	16
	Figure B.2 -- Connector wiring, 31-pin, 6 channels	17
	Figure B.3 -- Connector wiring, 21-pin, 3 channels (shoulder)	17
	Figure B.4 -- Connector wiring, 15-pin, 2 channels (elbow load cell)	18
	Figure B.5 -- Connector wiring, 15-pin, 1 channel (side exit, pubic)	18
	Figure B.6 -- 1-channel connector to G5 DAS	18
	Figure B.7 -- 2-channel connector to G5 DAS	19
	Figure B.8 -- 3-channel connector to G5 DAS	19
	Figure C.1 -- Linear accelerometer wiring	23
	Figure D.1 -- Head accelerometers	25
	Figure D.2 -- Upper neck load cell	26
	Figure D.3 -- Lower neck load cell	27
	Figure D.4 -- Thorax accelerometers	28
	Figure D.5 -- Rib displacement	29
	Figure D.6 -- Shoulder load cell	30
	Figure D.7 -- Arm accelerometers	31

Figure D.8 -- Arm sensors	32
Figure D.9 -- Pelvis accelerometers	33
Figure D.10 -- Lumbar spine load cell	34
Figure D.11 -- Sacro-iliac load cell	35
Figure D.12 -- Pubic load cell	36
Figure D.13 -- Femoral neck load cells	37
Figure D.14 -- Femur instrumentation	38
Figure D.15 -- Knee load cells	39
Figure D.16 -- Tibia instrumentation	40
Figure D.17 -- Tilt sensor channel orientations	41
Tables Table 1 -- Permissible WorldSID sensor locations and specifications	2
Table 2 -- DAS mass distribution	8
Table A.1 -- WorldSID load cell capacities	10