

ISO 13232-5:2005-12 (E)

Motorcycles - Test and analysis procedures for research evaluation of rider crash protective devices fitted to motorcycles - Part 5: Injury indices and risk/benefit analysis

Contents		Page
Foreword		vii
Introduction		viii
1	Scope	1
2	Normative references	2
3	Definitions and abbreviations	2
4	Requirements	3
4.1	Injury variables	3
4.2	Lower extremity injuries	4
4.3	Injury severity probabilities	4
4.4	Injury indices	5
4.5	Risk/benefit analysis	5
5	Procedures	5
5.1	Injury variables	5
5.2	Frangible component damage	10
5.3	Injury severity probabilities	10
5.4	Probability of discrete AIS injury severity level	15
5.5	Injury costs	17
5.6	Probability of fatality	18
5.7	Probable AIS	21
5.8	Normalized injury costs	22
5.9	Risk/benefit analysis	23
6	Documentation	27
Annex A (normative) Injury costs		28
Annex B (normative) Mortality rate		30
Annex C (informative) ICM Variable and subscript definitions		31
Annex D (informative) Example computer code of the injury cost model		34
Annex E (informative) Comparison of results to reference risk and benefit values		56
Annex F (informative) Example probable injury cost data		57
Annex G (informative) Probability distribution curves		69
Annex H (informative) Example cumulative distribution function plots		73
Annex I (informative) Example computer code for calculations of head contacts		74
Annex J (informative) AO/C1/C2 upper neck injury probabilities and injury cost		97

Annex K (informative) Estimated distribution of neck AO/C1/C2 injury severities in the LA/Hannover database	120
Annex L (informative) Distribution of maximum neck forces and moments from computer simulations of 498 LA/Hannover cases and 67 fatal USC cases	122
Annex M (informative) Injury criteria coefficient search algorithm used for neck injury criteria identification	124
Annex N (informative) Dummy neck computer simulation validation	131
Figures Figure 1 -- Chest potentiometer geometry shown for the upper sternum	8
Figure 2 -- Risk of life threatening brain injury for HIC for $t_2 - t_1 = 0,015$ s	21
Figure D.1 -- Flow diagram of the injury cost model	55
Figure G.1 -- Probability distribution of head injuries as a function of G_{max} (Kramer & Appel, 1990)	70
Figure G.2 -- Probability distribution of thoracic injury as a function of maximum resultant upper (or lower) sternum compression (Kroell, et al., 1974)	70
Figure G.3 -- Probability distribution of thoracic injuries as a function of maximum resultant upper (or lower) sternum velocity-compression (Lowne & Janssen, 1990)	71
Figure G.4 -- Probability distribution of human abdominal injuries as a function of maximum human abdominal penetration (Rouhana, et al., 1990)	71
Figure G.5 -- Probability distribution of neck injury as a function of $N_{II}max$	72
Figure H.1 -- Example of a continuous cumulative distribution function graph for change in an injury assessment variable	73
Figure H.2 -- Example of a discrete cumulative distribution function graph for change in an injury index	73
Figure J.1 -- Forces and moments at t_{max} from computer simulations of 67 USC fatal cases and the best step- wise fit envelopes of constant $N_{II}max$, providing the basis for the envelope shape	108
Figure J.2 -- Forces and moments at t_{max} from computer simulations of 498 LA and Hannover cases and envelopes of constant $N_{II}max$, providing the basis for the $N_{II}max$ vs 50% injury probability	110
Figure J.3 -- Critical tension force vs the coefficient, providing the basis for the $\alpha=3.1$	111
Figure J.4 -- Neck AO/C1/C2 injury risk curves for the new MATD neck	112
Figure J.5 -- Distribution of observed and predicted computer simulations	113
Figure J.6 -- Comparison of the general shape and axes of the injury criteria for the new MATD neck to the allowable limits proposed by NHTSA for the Hybrid III 50 PAM neck (recognizing that the necks have very different stiffnesses)	116
Figure J.7 -- Neck AIS 3 + injury risk vs tension for the Hybrid III P50 male neck (Mertz & Prasad 2000)	117
Figure J.8 -- Neck AIS 3 + injury risk vs combined tension and extension for the Hybrid III P50 male neck (Mertz & Prasad 2000)	118

Figure L.1 -- Maximum neck force and moment distributions for the new MATD neck (498 LA/Hannover cases and 67 USC fatal cases)	123
Figure M.1 -- Convergence of the global search algorithm	129
Figure M.2 -- Convergence of the local search algorithm	130
Figure N.1 -- Laboratory test and computer simulation of forward neck flexion at 0,1 s	133
Figure N.2 -- Forward neck flexion response of laboratory test and computer simulation	134
Figure N.3 -- Laboratory test and computer simulation of rearward neck extension at 0,1 s	135
Figure N.4 -- Rearward neck extension response of laboratory test and computer simulation	136
Figure N.5 -- Laboratory test and computer simulation of lateral neck flexion at 0,1 s	137
Figure N.6 -- Lateral neck flexion response of laboratory test and computer simulation	138
Figure N.7 -- Computer simulation of neck torsion test at 0,1 s	139
Figure N.8 -- Neck torsion response of laboratory test and computer simulation	140
Figure N.9 -- Neck axial force response of laboratory impact test and computer simulation	141
Figure N.10 -- Full scale test and computer simulation of impact configuration 413-0/30 0,1 s after initial contact	142
Figure N.11 -- Full scale test and computer simulation of 413-0/30 with new MATD neck	143
Tables Table 1a -- Closed head injury severity probability as a function of Gmax	12
Table 1b -- Closed head injury severity probability as a function of HIC	12
Table 2 -- Thoracic compression injury severity probability as a function of Cus,max and CIs,max ..	13
Table 3 -- Thoracic injury velocity-compression severity probability as a function of VCus,max and VCIs,max	13
Table 4 -- Intra-abdominal penetration injury severity probability as a function of PA,max	14
Table 5 -- Neck combined loading injury severity probability as a function of NII	14
Table 6 -- AIS injury severity level for frangible component damage	15
Table 7 -- Example PIE,j determination	16
Table 8 -- Permanent partial incapacity determination	16
Table 9 -- Injury probability and probable AIS	19
Table 10 -- Injury assessment variables, change in head injury potential, and injury indices to be calculated for each impact configuration	24
Table 11 -- Example table used to calculate the weighted cumulative distribution of change in maximum head acceleration due to a protective device	26
Table A.1 -- Medical costs	28
Table A.2 -- Ancillary costs	29
Table B.1 -- Mortality rates for all AIS combinations	30

Table C.1 -- Variable definitions	31
Table C.2 -- Body region subscript definition	32
Table C.3 -- Other subscripts	32
Table F.1 -- Legend for Table F.2	57
Table F.2 -- Example probable injury cost input/output results	58
Table J.1 -- Summary of Accident Databases	99
Table J.2 -- Distribution of neck AO/C1/C2 injuries in the USC fatal motorcycle accident database	103
Table J.3 -- Distribution of neck AO/C1/C2 injuries in the LA/Hannover database	105
Table J.4 -- Number of cases with observed and predicted injuries	105
Table J.5 -- Force and moment normalizing coefficients for the new MATD neck	106
Table J.6 -- Injury threshold coefficients for the 67 USC fatal cases with the new MATD neck	106
Table J.7 -- Comparison of number of observed and predicted injuries by injury severity and direction	107
Table J.8 -- Injury severity risk coefficients for the new MATD neck	109
Table J.9 -- Comparison of neck injury criteria for a 50th percentile male	115
Table K.1 -- Distribution of neck AO/C1/C2 injury severities in the LA/Hannover and USC Fatal Accident Databases	121