

# ISO 10368:2006-02 (E)

## Freight thermal containers - Remote condition monitoring

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | iv          |
| Introduction ..... |  | v           |
| 1                  | Scope .....  | 1           |
| 2                  | Normative references .....                                       | 1           |
| 3                  | Terms and definitions .....                                      | 1           |
| 4                  | Performance requirements .....                                   | 3           |
| 4.1                | General .....  | 3           |
| 4.2                | Requirements .....   | 3           |
| 4.2.1              | System components .....  | 3           |
| 4.2.2              | Performance function .....                                       | 4           |
| 4.2.3              | Performance constraints .....                                    | 8           |
| 5                  | System compatibility requirements .....                          | 9           |
| 5.1                | General .....  | 9           |
| 5.2                | Communications protocol .....                                    | 9           |
| 5.2.1              | General .....  | 9           |
| 5.2.2              | MMU to MDCU communications .....                                 | 9           |
| 5.2.3              | MDCU to LRCD communications .....                                | 33          |
| 5.2.4              | MDCU to HRCD communications .....                                | 42          |
| 5.3                | MMU/Device communications .....                                  | 50          |
| 5.3.1              | Headers .....  | 50          |
| 5.3.2              | Other MMU/Device messages .....                                  | 50          |
| 5.4                | Low data rate physical requirements -- LDCU to LRCD .....        | 51          |
| 5.4.1              | Frequency .....  | 51          |
| 5.4.2              | Modulation method .....  | 51          |
| 5.4.3              | Baud rate .....  | 51          |
| 5.4.4              | Transmission mode .....  | 51          |
| 5.4.5              | Injection mode .....   | 51          |
| 5.4.6              | Receiver sensitivity .....                                       | 51          |
| 5.4.7              | Non-transmission Impedance .....                                 | 51          |
| 5.4.8              | Bit synchronization .....  | 51          |
| 5.4.9              | Carrier setup time .....   | 51          |
| 5.4.10             | Out-of-band filtering for HDR compatibility .....                | 51          |
| 5.5                | High data rate physical requirements -- HDCU to HRCD .....       | 52          |
| 5.5.1              | Modulation method -- Broad band .....                            | 52          |
| 5.5.2              | Transmission mode .....  | 52          |
| 5.5.3              | Injection mode .....   | 53          |
| 5.5.4              | Output/input impedance .....                                     | 53          |
| 5.5.5              | Power density function .....                                     | 53          |
| 5.5.6              | Synchronization method .....                                     | 53          |
| 5.5.7              | Demodulation method .....  | 53          |
| 5.5.8              | Receiver sensitivity .....                                       | 53          |
| 5.5.9              | Data link protocol .....   | 54          |
| 5.5.10             | Out-of-band filtering requirements for "LDR" compatibility ..... | 61          |
| Bibliography ..... |  | 64          |