ISO 10368:2006-02 (E)

Freight thermal containers - Remote condition monitoring

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Performance requirements 3
4.1 General 3
4.2 Requirements 3
4.2.1 System components 3
4.2.2 Performance function 4
4.2.3 Performance constraints 8

5 System compatibility requirements 9
5.1 General 9
5.2 Communications protocol 9
5.2.1 General 9
5.2.2 MMU to MDCU communications 9
5.2.3 MDCU to LRCD communications 33
5.2.4 MDCU to HRCD communications 42
5.3 MMU/Device communications 50
5.3.1 Headers 50
5.3.2 Other MMU/Device messages 50
5.4 Low data rate physical requirements -- LDCU to LRCD 51
5.4.1 Frequency 51
5.4.2 Modulation method 51
5.4.3 Baud rate 51
5.4.4 Transmission mode 51
5.4.5 Injection mode 51
5.4.6 Receiver sensitivity 51
5.4.7 Non-transmission Impedance 51
5.4.8 Bit synchronization 51
5.4.9 Carrier setup time 51
5.4.10 Out-of-band filtering for HDR compatibility 51
5.5 High data rate physical requirements -- HDCU to HRCD 52
5.5.1 Modulation method -- Broad band 52
5.5.2 Transmission mode 52
5.5.3 Injection mode 53
5.5.4 Output/input impedance 53
5.5.5 Power density function 53
5.5.6 Synchronization method 53
5.5.7 Demodulation method 53
5.5.8 Receiver sensitivity 53
5.5.9 Data link protocol 54
5.5.10 Out-of-band filtering requirements for "LDR" compatibility 61

Bibliography 64