# ISO 4930:2006-07 (E)

## Road vehicles - Elastomeric seals for hydraulic disc brake cylinders using a non-petroleum base hydraulic brake fluid (Service temperature 150° C max.)

## Contents

Page


Foreword ..... iv

1 Scope ..... 1

2 Normative references ..... 1

3 Product requirements ..... 1

4 Brake test fluid ..... 1

5 Apparatus ..... 2
5.1 Apparatus for test of resistance to fluid at elevated temperature, physical stability and precipitation characteristics ..... 2
5.2 Apparatus for high-temperature stroking test (see Figure 1) ..... 2
5.3 Apparatus for low-temperature leakage test (see Figure 2) ..... 3

6 Test requirements ..... 3

7 Preparation of test specimens ..... 4

8 Resistance to fluid at elevated temperature ..... 4
8.1 Test specimens ..... 4
8.2 Test procedure ..... 5

9 Resistance to fluid at elevated temperature - Precipitation characteristics ..... 5
9.1 Test specimens ..... 5
9.2 Test procedure ..... 5

10 Resistance to elevated temperature in dry air ..... 6
10.1 Test specimens ..... 6
10.2 Test procedure ..... 6

11 Ambient-temperature stroking test ..... 6
11.1 Test specimens ..... 6
11.2 Test procedure ..... 6

12 High-temperature stroking test ..... 7
12.1 Test specimens ..... 7
12.2 Test procedure ..... 7

13 Low-temperature leakage test ..... 8
13.1 Test specimens ..... 8
13.2 Test procedure ..... 8
13.3 Bent test procedure ..... 9

14 Cycling humidity storage corrosion test ..... 9
14.1 Test specimens ..... 9
14.2 Test procedure ..... 9