

# ISO 4930:2006-07 (E)

## Road vehicles - Elastomeric seals for hydraulic disc brake cylinders using a non-petroleum base hydraulic brake fluid (Service temperature 150° C max.)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Product requirements .....</b>	<b>1</b>
<b>4</b>	<b>Brake test fluid .....</b>	<b>1</b>
<b>5</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5.1</b>	<b>Apparatus for test of resistance to fluid at elevated temperature, physical stability and precipitation characteristics .....</b>	<b>2</b>
<b>5.2</b>	<b>Apparatus for high-temperature stroking test (see Figure 1) .....</b>	<b>2</b>
<b>5.3</b>	<b>Apparatus for low-temperature leakage test (see Figure 2) .....</b>	<b>3</b>
<b>6</b>	<b>Test requirements .....</b>	<b>3</b>
<b>7</b>	<b>Preparation of test specimens .....</b>	<b>4</b>
<b>8</b>	<b>Resistance to fluid at elevated temperature .....</b>	<b>4</b>
<b>8.1</b>	<b>Test specimens .....</b>	<b>4</b>
<b>8.2</b>	<b>Test procedure .....</b>	<b>5</b>
<b>9</b>	<b>Resistance to fluid at elevated temperature - Precipitation characteristics .....</b>	<b>5</b>
<b>9.1</b>	<b>Test specimens .....</b>	<b>5</b>
<b>9.2</b>	<b>Test procedure .....</b>	<b>5</b>
<b>10</b>	<b>Resistance to elevated temperature in dry air .....</b>	<b>6</b>
<b>10.1</b>	<b>Test specimens .....</b>	<b>6</b>
<b>10.2</b>	<b>Test procedure .....</b>	<b>6</b>
<b>11</b>	<b>Ambient-temperature stroking test .....</b>	<b>6</b>
<b>11.1</b>	<b>Test specimens .....</b>	<b>6</b>
<b>11.2</b>	<b>Test procedure .....</b>	<b>6</b>
<b>12</b>	<b>High-temperature stroking test .....</b>	<b>7</b>
<b>12.1</b>	<b>Test specimens .....</b>	<b>7</b>
<b>12.2</b>	<b>Test procedure .....</b>	<b>7</b>
<b>13</b>	<b>Low-temperature leakage test .....</b>	<b>8</b>
<b>13.1</b>	<b>Test specimens .....</b>	<b>8</b>
<b>13.2</b>	<b>Test procedure .....</b>	<b>8</b>
<b>13.3</b>	<b>Bent test procedure .....</b>	<b>9</b>
<b>14</b>	<b>Cycling humidity storage corrosion test .....</b>	<b>9</b>
<b>14.1</b>	<b>Test specimens .....</b>	<b>9</b>
<b>14.2</b>	<b>Test procedure .....</b>	<b>9</b>