

# ISO 6118:2006-07 (E)

Road vehicles - Elastomeric cups and seals for cylinders for hydraulic braking systems using a non-petroleum base hydraulic brake fluid (service temperature 70 °C max.)

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>General requirements .....</b>	<b>2</b>
<b>4.1</b>	<b>Workmanship and finish .....</b>	<b>2</b>
<b>4.2</b>	<b>Marking .....</b>	<b>2</b>
<b>4.3</b>	<b>Packaging .....</b>	<b>2</b>
<b>4.4</b>	<b>Sampling .....</b>	<b>2</b>
<b>5</b>	<b>Test requirements .....</b>	<b>2</b>
<b>5.1</b>	<b>Resistance to fluid at elevated temperature .....</b>	<b>2</b>
<b>5.2</b>	<b>Precipitation .....</b>	<b>2</b>
<b>5.3</b>	<b>Wheel cylinder seals heat pressure stroking .....</b>	<b>2</b>
<b>5.4</b>	<b>Master cylinder seals heat pressure stroking .....</b>	<b>3</b>
<b>5.5</b>	<b>Low temperature performance .....</b>	<b>4</b>
<b>5.6</b>	<b>Oven ageing .....</b>	<b>4</b>
<b>5.7</b>	<b>Corrosion .....</b>	<b>5</b>
<b>5.8</b>	<b>Storage corrosion test .....</b>	<b>5</b>
<b>6</b>	<b>Test procedures .....</b>	<b>5</b>
<b>6.1</b>	<b>Resistance to fluid at elevated temperature -- Dimensional test .....</b>	<b>5</b>
<b>6.2</b>	<b>Precipitation test .....</b>	<b>7</b>
<b>6.3</b>	<b>Wheel cylinder seals heat pressure stroking .....</b>	<b>8</b>
<b>6.4</b>	<b>Master cylinder seals heat pressure stroking .....</b>	<b>10</b>
<b>6.5</b>	<b>Low temperature performance .....</b>	<b>12</b>
<b>6.6</b>	<b>Oven ageing .....</b>	<b>13</b>
<b>6.7</b>	<b>Hardness determination .....</b>	<b>13</b>
<b>6.8</b>	<b>Corrosion test .....</b>	<b>13</b>
<b>6.9</b>	<b>Storage corrosion test .....</b>	<b>15</b>
	<b>Bibliography .....</b>	<b>16</b>