

ISO 4928:2006-07 (E)

Road vehicles - Elastomeric cups and seals for cylinders for hydraulic braking systems using a non-petroleum base hydraulic brake fluid (Service temperature 120 °C max.)

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General requirements	2
4.1 Workmanship and finish	2
4.2 Marking	2
4.3 Packaging	2
4.4 Sampling	2
5 Test requirements	2
5.1 Resistance to fluid at elevated temperature	2
5.2 Precipitation	2
5.3 Wheel cylinder seals heat pressure stroking	2
5.4 Master cylinder seals heat pressure stroking	3
5.5 Low-temperature performance	4
5.6 Oven ageing	4
5.7 Corrosion	4
5.8 Storage corrosion test	5
6 Test procedures	5
6.1 Resistance to fluid at elevated temperature -- Dimensional test	5
6.2 Precipitation test	7
6.3 Wheel cylinder seals heat pressure stroking	8
6.4 Master cylinder seals heat pressure stroking	9
6.5 Low-temperature performance	11
6.6 Oven ageing	12
6.7 Hardness determination	12
6.8 Corrosion test	13
6.9 Storage corrosion test	14