

ISO 6119:2006-08 (E)

Road vehicles - Elastomeric seals for hydraulic disc brake cylinders using a non-petroleum base hydraulic brake fluid (Service temperature 120 °C max.)

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Product requirements	1
4	Brake test fluid	1
5	Apparatus	2
5.1	Apparatus for test of resistance to fluid at elevated temperature, physical stability and precipitation characteristics	2
5.2	Apparatus for high-temperature stroking test (see Figure 1)	2
5.3	Apparatus for low-temperature leakage test (see Figure 2)	3
6	Test requirements	3
7	Preparation of test specimens	4
8	Resistance to fluid at elevated temperature -- Physical stability	4
8.1	Test specimens	4
8.2	Test procedure	4
9	Resistance to fluid at elevated temperature -- Precipitation characteristics	5
9.1	Test specimens	5
9.2	Test procedure	5
10	Resistance to elevated temperature in dry air	6
10.1	Test specimens	6
10.2	Test procedure	6
11	Ambient-temperature stroking test	6
11.1	Test specimens	6
11.2	Test procedure	6
12	High-temperature stroking test	7
12.1	Test specimens	7
12.2	Test procedure	7
13	Low-temperature leakage test	8
13.1	Test specimens	8
13.2	Test procedure	8
13.3	Bend test procedure	9
14	Cycling humidity storage corrosion test	9
14.1	Test specimens	9
14.2	Test procedure	9