

ISO 6119:2006-08 (E)

Road vehicles - Elastomeric seals for hydraulic disc brake cylinders using a non-petroleum base hydraulic brake fluid (Service temperature 120 °C max.)

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Product requirements | 1 |
| 4 | Brake test fluid | 1 |
| 5 | Apparatus | 2 |
| 5.1 | Apparatus for test of resistance to fluid at elevated temperature, physical stability and precipitation characteristics | 2 |
| 5.2 | Apparatus for high-temperature stroking test (see Figure 1) | 2 |
| 5.3 | Apparatus for low-temperature leakage test (see Figure 2) | 3 |
| 6 | Test requirements | 3 |
| 7 | Preparation of test specimens | 4 |
| 8 | Resistance to fluid at elevated temperature -- Physical stability | 4 |
| 8.1 | Test specimens | 4 |
| 8.2 | Test procedure | 4 |
| 9 | Resistance to fluid at elevated temperature -- Precipitation characteristics | 5 |
| 9.1 | Test specimens | 5 |
| 9.2 | Test procedure | 5 |
| 10 | Resistance to elevated temperature in dry air | 6 |
| 10.1 | Test specimens | 6 |
| 10.2 | Test procedure | 6 |
| 11 | Ambient-temperature stroking test | 6 |
| 11.1 | Test specimens | 6 |
| 11.2 | Test procedure | 6 |
| 12 | High-temperature stroking test | 7 |
| 12.1 | Test specimens | 7 |
| 12.2 | Test procedure | 7 |
| 13 | Low-temperature leakage test | 8 |
| 13.1 | Test specimens | 8 |
| 13.2 | Test procedure | 8 |
| 13.3 | Bend test procedure | 9 |
| 14 | Cycling humidity storage corrosion test | 9 |
| 14.1 | Test specimens | 9 |
| 14.2 | Test procedure | 9 |