

DIN EN 13438:2013-12 (E)

Paints and varnishes - Powder organic coatings for hot dip galvanised or sherardised steel products for construction purposes

| Contents | | Page |
|----------------------------|--|-------------|
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Substrate material | 8 |
| 5 | Coating powder | 8 |
| 5.1 | Identification | 8 |
| 5.2 | Storage | 8 |
| 5.3 | Performance requirements | 9 |
| 5.3.1 | General | 9 |
| 5.3.2 | Colour | 9 |
| 5.3.3 | Gloss | 9 |
| 5.3.4 | Adhesion | 9 |
| 5.3.5 | Resistance to scratching | 9 |
| 5.3.6 | Resistance to deformation | 9 |
| 5.3.7 | Resistance to mortar | 9 |
| 5.3.8 | Resistance to weathering | 9 |
| 5.3.9 | Resistance to humidity | 10 |
| 5.3.10 | Resistance to sulfur dioxide | 10 |
| 5.3.11 | Permeability | 10 |
| 5.3.12 | Resistance to salt spray | 10 |
| 5.4 | Health and safety information | 10 |
| 6 | Application | 11 |
| 6.1 | Cleaning and pretreatment of the hot dip galvanised or sherardised substrate | 11 |
| 6.2 | Coating powder | 11 |
| 6.3 | Application of coating powder | 11 |
| 6.4 | Significant surfaces of coated article | 11 |
| 6.5 | Performance requirements of the powder coated article | 11 |
| 6.5.1 | General | 11 |
| 6.5.2 | Surface appearance | 11 |
| 6.5.3 | Colour | 11 |
| 6.5.4 | Thickness | 11 |
| 6.5.5 | Gloss | 12 |
| 6.5.6 | Adhesion | 12 |
| 7 | Certificate of conformity | 12 |
| Annex A (normative) | Methods of test for coating powders | 15 |
| A.1 | General | 15 |
| A.2 | Sampling | 15 |
| A.3 | Coated test panels | 15 |
| A.3.1 | Material and dimensions | 15 |

| | | |
|--|---|----|
| A.3.2 | Pretreatment | 15 |
| A.3.3 | Coating of the test panels | 15 |
| A.3.4 | Determination of thickness | 15 |
| A.3.5 | Appearance and conditioning | 16 |
| A.4 | Test procedures on coated test panels | 16 |
| A.4.1 | Surface | 16 |
| A.4.2 | Colour | 16 |
| A.4.3 | Gloss | 16 |
| A.4.4 | Adhesion | 16 |
| A.4.5 | Resistance to scratching | 17 |
| A.4.6 | Resistance to deformation | 17 |
| A.4.7 | Resistance to mortar | 17 |
| A.4.8 | Resistance to weathering | 17 |
| A.4.9 | Resistance to humidity | 17 |
| A.4.10 | Resistance to sulfur dioxide | 18 |
| A.4.11 | Permeability | 18 |
| A.4.12 | Resistance to salt spray | 18 |
| Annex B (informative) Guidance on cleaning and pretreatment processes | | 19 |
| B.1 | Cleaning | 19 |
| B.2 | Pretreatment | 19 |
| B.3 | Types of pretreatment | 19 |
| B.3.1 | Conversion and drying of the conversion coating (chemical pretreatment) | 19 |
| B.3.2 | Mechanical pretreatment | 20 |
| Annex C (informative) Guidelines on the powder coating process | | 21 |
| Annex D (normative) Methods of test for powder coatings | | 22 |
| D.1 | General | 22 |
| D.2 | Test piece preparation | 22 |
| D.3 | Test procedures on finished articles | 22 |
| D.3.1 | Surface appearance | 22 |
| D.3.2 | Colour | 22 |
| D.3.3 | Thickness | 22 |
| D.3.4 | Gloss | 22 |
| D.3.5 | Adhesion | 22 |
| D.4 | Test procedures on test panels | 23 |
| Annex E (informative) Guidelines on the care and protection of powder coated hot dip galvanised or sherardised steel components | | 24 |
| E.1 | Packing and handling | 24 |
| E.2 | Tapes | 24 |
| Bibliography | | 25 |