# DIN EN ISO 11890-2:2013-07 (E)

## Paints and varnishes - Determination of volatile organic compound (VOC) content - Part 2: Gas-chromatog raphic method (ISO 11890-2:2013)

## Contents

Page


Foreword ..... 3

1 Scope ..... 4

2 Normative references ..... 4

3 Terms and definitions ..... 4

4 Principle ..... 5

5 Required supplementary information ..... 5

6 Apparatus ..... 5
6.1 Gas chromatograph ..... 5
6.2 Sample injection system ..... 6
6.3 Oven ..... 6
6.4 Detector ..... 6
6.5 Capillary column ..... 7
6.6 Qualitative-analysis equipment ..... 7
6.7 Injection syringe ..... 7
6.8 Chart recorder ..... 7
6.9 Integrator ..... 7
6.10 Sample vials ..... 7
6.11 Gas filters ..... 7
6.12 Gases ..... 7

7 Reagents ..... 8
7.1 Internal standard ..... 8
7.2 Calibration compounds ..... 8
7.3 Dilution solvent ..... 8
7.4 Marker compound ..... 8

8 Sampling ..... 8

9 Procedure ..... 8
9.1 Density ..... 8
9.2 Water content ..... 9
9.3 Gas-chromatographic conditions ..... 9
9.4 Qualitative analysis of product ..... 9
9.5 Calibration ..... 9
9.6 Sample preparation ..... 10
9.7 Quantitative determination of compound content ..... 10

10 Calculation ..... 11
10.1 General ..... 11
10.2 Method 1: VOC content, as a percentage by mass, of the product "ready for use" ..... 11
10.3 Method 2: VOC content, in grams per litre, of the product "ready for use" ..... 12
10.4 Method 3: VOC content, in grams per litre, of the product "ready for use" less water ..... 12
10.5 Method 4: VOC content, in grams per litre, of the product "ready for use" less water and less exempt compounds (only required if national legislation applies) ..... 13

11 Expression of results ..... 13

12 Precision ..... 13
12.1 General ..... 13
12.2 Repeatability limit r ..... 13
12.3 Reproducibility limit R ..... 14

13 Test report ..... 14

Annex A (normative) Required supplementary information ..... 15

Annex B (informative) Examples of gas-chromatographic conditions ..... 16

Bibliography ..... 20