ISO 16773-2:2016-04 (E)

Electrochemical impedance spectroscopy (EIS) on coated and uncoated metallic specimens - Part 2: Collection of data

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Principle 1

5 Electrochemical cell 2
5.1 General 2
5.2 Electrodes 3
5.3 Exposed area 3
5.4 Electrolyte 3

6 Procedure 4
6.1 Grounding 4
6.2 Shielding 4
6.3 Cell cable ground contacts 4
6.4 Local conditions 4
6.5 Measurement equipment characteristics 5
6.6 Confidence test 5
6.6.1 General 5
6.6.2 Use of interlaboratory test cells for confidence test 6
6.6.3 Error estimate and accuracy 6
6.7 Specimens 6
6.7.1 Preconditioning of specimens 6
6.7.2 Environmental control 6
6.8 Evaluation of laboratory and field coating specimens 6
6.9 Number of specimens and repeatability of results 7

7 Instrumental parameters 7
7.1 General 7
7.2 Conditioning potential and conditioning time 8
7.3 Frequency spectrum 8
7.4 Data point spacing and points per decade 8
7.5 D.C. potential control 8
7.6 Amplitude of perturbation 9
7.7 Current range settings 9
7.8 Data averaging settings 9

8 Data presentation 9
8.1 General 9
8.2 Bode plot 9
8.3 Nyquist plot 10

9 Exchangefileformat 11

10 Test report 11

Annex A (informative) Determination of maximum measurable impedance with the open- lead test 13

Annex B (normative)Dataexchangefileformat 15

Annex C (informative) Considerations about the precise determination of the exposed area 19

Bibliography 24