

DIN EN ISO 6504-3:2020-04 (E)

Paints and varnishes - Determination of hiding power - Part 3: Determination of hiding power of paints for masonry, concrete and interior use (ISO 6504-3:2019)

Contents		Page
European foreword		3
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Symbols and abbreviated terms	7
5	Principle	9
6	Apparatus	9
7	Sampling	11
8	Procedure and calculation	12
8.1	Preparation of substrate	12
8.1.1	Method A (foil)	12
8.1.2	Method B and Method C (black and white charts)	12
8.2	Preparation of coated foils or black and white charts	12
8.3	Determination of the spreading rate of the test specimen	12
8.3.1	Calculation of the surface mass density	12
8.3.2	Determination of the density	14
8.3.3	Determination of the non-volatile matter	14
8.3.4	Calculation of the theoretical dry- or wet-film thickness (method A, method B and method C)	14
8.3.5	Calculation 1 – Determination of the theoretical spreading rate by calculation from the non-volatile matter content determined in accordance with ISO 3251 and the density of the coating material (see ISO 3233-3) (method A and method B)	15
8.3.6	Calculation 2 – Determination of the theoretical spreading rate calculated with the different coated masses on the two charts (method C), the density of the coating material according to ISO 2811 (all parts) and the coated area	17
8.4	Measurement of tristimulus value Y_{10} and calculation of the hiding power H_{10}	18
8.4.1	General	18
8.4.2	Method A (foil)	18
8.4.3	Method B (black and white charts)	18
8.4.4	Method C (black and white charts)	18
8.5	Graphical method for determination of the hiding power at a given spreading rate (method C)	19
8.5.1	General	19
8.5.2	Determination by graphical method	19
8.5.3	Determination by calculation with a known slope	21
9	Designation of the test result	22
10	Precision	23
11	Test report	23
Annex A (informative) Details on interlaboratory comparison		24
Bibliography		26