ISO 6504-3:2019-11 (E)

Paints and varnishes - Determination of hiding power - Part 3: Determination of hiding power of paints for masonry, concrete and interior use

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols and abbreviated terms 2

5 Principle 4

6 Apparatus 4

7 Sampling 6

8 Procedure and calculation 7
8.1 Preparation of substrate 7
8.1.1 Method A (foil) 7
8.1.2 Method B and Method C (black and white charts) 7
8.2 Preparation of coated foils or black and white charts 7
8.3 Determination of the spreading rate of the test specimen 7
8.3.1 Calculation of the surface mass density 7
8.3.2 Determination of the density 9
8.3.3 Determination of the non-volatile matter 9
8.3.4 Calculation of the theoretical dry- or wet-film thickness (method A, method B and method C) 9
8.3.5 Calculation 1 - Determination of the theoretical spreading rate by calculation from the non-volatile matter content determined in accordance with ISO 3251 and the density of the coating material (see ISO 3233-3) (method A and method B) 10
8.3.6 Calculation 2 - Determination of the theoretical spreading rate calculated with the different coated masses on the two charts (method C), the density of the coating material according to ISO 2811 (all parts) and the coated area 12
8.4 Measurement of tristimulus value Y10 and calculation of the hiding power H10 13
8.4.1 General 13
8.4.2 Method A (foil) 13
8.4.3 Method B (black and white charts) 13
8.4.4 Method C (black and white charts) 13
8.5 Graphical method for determination of the hiding power at a given spreading rate (method C) 14
8.5.1 General 14
8.5.2 Determination by graphical method 14
8.5.3 Determination by calculation with a known slope 16

9 Designation of the test result 17

10 Precision 18

11 Test report 18

Annex A (informative) Details on interlaboratory comparison 20

Bibliography 22