

# DIN EN ISO 1518-1:2023-05 (E)

## Paints and varnishes - Determination of scratch resistance - Part 1: Constant-loading method (ISO 1518-1:2023)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
Foreword.....		4
<b>1</b>	<b>Scope</b> .....	<b>5</b>
<b>2</b>	<b>Normative references</b> .....	<b>5</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>5</b>
<b>4</b>	<b>Principle</b> .....	<b>6</b>
<b>5</b>	<b>Apparatus</b> .....	<b>6</b>
<b>6</b>	<b>Sampling</b> .....	<b>7</b>
<b>7</b>	<b>Test panels</b> .....	<b>8</b>
	7.1 Substrate.....	8
	7.2 Preparation and coating.....	8
	7.3 Drying and conditioning.....	8
	7.4 Thickness of coating.....	9
<b>8</b>	<b>Procedure</b> .....	<b>9</b>
	8.1 Test conditions.....	9
	8.2 General test procedure.....	9
	8.3 Procedure for a single specified load (“pass/fail” test).....	9
	8.4 Procedure for determination of the minimum load to cause penetration.....	9
	8.5 Evaluation of the scribe.....	10
<b>9</b>	<b>Precision</b> .....	<b>10</b>
<b>10</b>	<b>Test report</b> .....	<b>10</b>
<b>Annex A (informative) Comparison of the designation of the scratch styli in the different editions of ISO 1518-1</b> .....		<b>12</b>
<b>Bibliography</b> .....		<b>13</b>