

DIN EN ISO 1518-1:2023-05 (E)

Paints and varnishes - Determination of scratch resistance - Part 1: Constant-loading method (ISO 1518-1:2023)

| Contents | | Page |
|---|---|-------------|
| European foreword | | 3 |
| Foreword..... | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Principle | 6 |
| 5 | Apparatus | 6 |
| 6 | Sampling | 7 |
| 7 | Test panels | 8 |
| | 7.1 Substrate..... | 8 |
| | 7.2 Preparation and coating..... | 8 |
| | 7.3 Drying and conditioning..... | 8 |
| | 7.4 Thickness of coating..... | 9 |
| 8 | Procedure | 9 |
| | 8.1 Test conditions..... | 9 |
| | 8.2 General test procedure..... | 9 |
| | 8.3 Procedure for a single specified load (“pass/fail” test)..... | 9 |
| | 8.4 Procedure for determination of the minimum load to cause penetration..... | 9 |
| | 8.5 Evaluation of the scribe..... | 10 |
| 9 | Precision | 10 |
| 10 | Test report | 10 |
| Annex A (informative) Comparison of the designation of the scratch styli in the different editions of ISO 1518-1 | | 12 |
| Bibliography | | 13 |