

DIN EN ISO 4624:2023-09 (E)

Paints and varnishes - Pull-off test for adhesion (ISO 4624:2023)

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 3 |
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Principle | 7 |
| 5 | Apparatus | 7 |
| 6 | Adhesives | 10 |
| 7 | Sampling | 11 |
| 8 | Test panels | 11 |
| 8.1 | Substrate | 11 |
| 8.2 | Preparation and coating | 11 |
| 8.3 | Drying and conditioning | 11 |
| 8.4 | Thickness of coating | 11 |
| 9 | Procedure | 11 |
| 9.1 | Number of determinations | 11 |
| 9.2 | Ambient conditions | 11 |
| 9.3 | Adhesive | 11 |
| 9.4 | Test assemblies | 12 |
| 9.4.1 | Method A: General method (using two dollies) for testing both rigid and deformable substrates | 12 |
| 9.4.2 | Method B: Method for testing from one side only, using a single dolly (suitable for rigid substrates only) | 12 |
| 9.4.3 | Method C: Method using dollies, one as a painted substrate | 13 |
| 9.5 | Measurement | 14 |
| 9.5.1 | Breaking strength | 14 |
| 9.5.2 | Nature of the fracture | 14 |
| 10 | Calculation and expression of results | 14 |
| 10.1 | Breaking strength | 14 |
| 10.2 | Nature of failure | 15 |
| 10.3 | Example | 15 |
| 11 | Precision | 15 |
| 12 | Test report | 15 |
| Bibliography | | 17 |