

DIN EN ISO 17895:2024-11 (E)

Paints and varnishes - Determination of volatile organic compound (VOC) - Gas-chromatographic method with headspace injection for VOC determination (ISO 17895:2024)

Contents		Page
European foreword		3
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Principle	7
5	Required information	7
6	Apparatus	7
7	Reagents	9
8	Procedure	10
8.1	Number of determinations	10
8.2	Sample preparation	10
8.2.1	General	10
8.2.2	Dilution of original sample	10
8.2.3	Preparation of test samples for analysis without multiple standard additions	10
8.2.4	Preparation of test samples for analysis with multiple standard additions	10
8.3	Analysis	11
8.3.1	General	11
8.3.2	Headspace injector	11
8.3.3	Gas chromatograph	11
8.3.4	Determination of integration end point	12
9	Evaluation	12
10	Calculation	13
10.1	General	13
10.2	Method 1: VOC content, as a percentage by mass, of the product "ready for use"	13
10.3	Method 2: VOC content, in grams per litre, of the product "ready for use"	14
11	Precision	15
11.1	General	15
11.2	Repeatability limit, <i>r</i>	15
11.3	Reproducibility limit, <i>R</i>	16
12	Test report	16
Annex A (informative) Gas chromatogram of the reference compound mixture and tetradecane		17
Bibliography		18