DIN EN 14648:2007-12 (E)

Building hardware - Fittings for shutters - Requirements and test methods

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 6

4 Classification 7
4.1 General 7
4.2 Category of use (first digit) 7
4.3 Durability (second digit) 7
4.4 Mass (third digit) 7
4.5 Fire resistance (fourth digit) 8
4.6 Safety in use (fifth digit) 8
4.7 Corrosion resistance (sixth digit) 8
4.8 Example of classification of shutter hardware 8

5 Requirements 8
5.1 Dangerous substances 8
5.2 Category of use (first digit) 8
5.3 Durability (second digit) 9
5.4 Mass (third digit) 9
5.5 Fire resistance (fourth digit) 9
5.6 Safety in use (fifth digit) 9
5.7 Corrosion resistance (sixth digit) 10

6 Test equipment 11
6.1 Test rig 11
6.2 Beam to accommodate the frame hinges 11
6.3 Essentially the beam has a cross-section of (100 × 100) mm, and a length of 1 600 mm. Test shutter 12
6.4 Moving device 12

7 Test method) 13
7.1 Samples 13
7.2 Procedures 13
7.3 Durability test 13
7.4 Overload tests) 14
7.5 Corrosion resistance test 15

8 Marking 15

Annex A (informative) Shutter hardware terminology 16

Annex B (informative) Deviation after the durability test 18

Annex C (informative) Test equipment 19

Annex D (normative) Flow chart of test procedures 22

Bibliography 23