DIN EN 12602:2008-08 (E)

Prefabricated reinforced components of autoclaved aerated concrete

Contents

Page

Foreword 9

1 Scope 11

2 Normative references 11

3 Terms, definitions, symbols and abbreviations 13
3.1 Terms and definitions 13
3.2 Symbols 14
3.2.1 General symbols 14
3.2.2 Subscripts 14
3.2.3 Symbols used in this European Standard (including normative annexes, except Annex C) 15
3.3 Abbreviations 20

4 Properties and requirements of materials 21
4.1 Constituent materials of autoclaved aerated concrete 21
4.1.1 General 21
4.1.2 Release of dangerous substances 21
4.2 Autoclaved aerated concrete parameters 22
4.2.1 General 22
4.2.2 Dry density 22
4.2.3 Characteristic strength values 23
4.2.4 Compressive strength 23
4.2.5 Tensile strength and flexural strength 24
4.2.6 Stress-strain diagram 24
4.2.7 Modulus of elasticity 24
4.2.8 Poisson's ratio 25
4.2.9 Coefficient of thermal expansion 25
4.2.10 Drying shrinkage 25
4.2.11 Creep 25
4.2.12 Specific heat 26
4.2.13 Thermal conductivity 26
4.2.14 Water vapour permeability 28
4.2.15 Water tightness 28
4.3 Reinforcement 28
4.3.1 Steel 28
4.3.2 Structural reinforcement 28
4.3.3 Effective diameter of coated bars 29
4.3.4 Non-structural reinforcement 29
4.4 Bond 30
4.5 Thermal prestress 30
4.5.1 General 30
4.5.2 Declared mean initial prestrain 0m,g 31

5 Properties and requirements of components 31
5.1 General 31
5.1.1 Mechanical resistance 31
5.1.2 Acoustic properties 31
5.1.3 Reaction to fire and resistance to fire 32
5.1.4 Design thermal resistance and design thermal conductivity 32
5.2 Technical requirements and declared properties 32

5.2.1 Dimensions and tolerances 32
5.2.2 Mass of the components 33
5.2.3 Dimensional stability 33
5.2.4 Load-bearing capacity 34
5.2.5 Deflections 34
5.2.6 Joint strength 35
5.2.7 Minimum requirements 35
5.3 Durability 37
5.3.1 General 37
5.3.2 Environmental conditions 37
5.3.3 Corrosion protection of reinforcement 38
5.3.4 Freeze and thaw resistance 39

6 Evaluation of conformity 39
6.1 Introduction 39
6.2 Initial type-testing of the component 39
6.3 Factory production control 40
6.3.1 General 40
6.3.2 Process control 40
6.3.3 Finished products 41
6.4 Initial inspection of the factory and the factory production control 41
6.4.1 Information to be supplied 41
6.4.2 Inspection 41
6.4.3 Reports 41
6.5 Surveillance, assessment and acceptance of the factory production control 42
6.5.1 Inspection tasks 42
6.5.2 Frequency of inspections 42
6.5.3 Reports 42
6.6 Actions to be taken in the event of non-conformity 42

7 Basis for design 48
7.1 Design methods 48
7.2 Limit states 48
7.3 Actions 48

8 Marking, labelling and designation 49
8.1 Standard designation 49
8.2 Production detail information 49
8.3 Additional information on accompanying documents 49

A.1 General 51
A.2 Ultimate limit states (ULS) General design assumptions 51
A.3 Ultimate limit states (ULS): design for bending and combined bending and axial compression 53
A.3.1 Design assumptions 53
A.3.2 Stress-strain diagram for AAC 53
A.3.3 Stress-strain diagram for reinforcing steel 54
A.3.4 Minimum reinforcement 56
A.4 Shear 57
A.4.1 Shear design for components predominantly under transverse load 57
A.5 Ultimate limit states induced by structural deformation (buckling) 62
A.5.1 General 62
A.5.2 Method based on Euler formula 62
A.5.3 Modified model column method 63
A.6 Punching 69
A.6.1 General 69
A.6.2 Scope and definitions 69
A.6.3 Design method for punching shear 71
A.7 Primary torsion/combined primary torsion and shear 72
A.8 Concentrated forces 74
A.9 Serviceability limit states (SLS) 75
A.9.1 General 75

A.9.2 Limitation of stresses under serviceability conditions 75
A.9.3 Serviceability limit states of cracking 76
A.9.4 Serviceability limit states of deformation 76
A.10 Detailing of reinforcement 79
A.10.1 General 79
A.10.2 Bond 79

Annex A (normative) Design by calculation 51
A.10.3 Anchorage 80
A.11 Support length 82

B.1 General 84
B.2 Safety evaluation 85
B.2.1 General 85
B.2.2 Brittle and ductile failure 85
B.3 Ultimate limit state 85
B.3.1 General 85
B.3.2 Transversely loaded components 85
B.3.3 Longitudinally loaded components 87
B.3.4 Simultaneously transversely and longitudinally loaded wall components 90
B.3.5 Anchorage 91
B.4 Serviceability limit states 93
B.4.1 Crack width control 93
B.4.2 Deformations 93

C.1 General 94
C.1.1 Scope 94
C.1.2 Distinction between principles and application rules 94
C.1.3 Terms and definitions 94
C.1.4 Symbols 96
C.1.5 Units 97
C.2 Basic principles 97
C.2.1 Performance requirements 97
C.2.2 Design values of material properties 98
C.2.3 Assessment methods 98
C.3 Material properties 99
C.3.1 General 99
C.3.2 AAC 99
C.3.3 Steel 101
C.4 Structural fire design methods 102
C.4.1 General 102
C.4.2 Tabulated data 102
C.4.3 Simplified design methods 106
C.4.4 Anchorage 110
C.5 Protective layers 110

elevated temperature 111

CB.1 Floor and roof components with dry joints 114

CB.2 Floor and roof components with mortar joints 114

CB.3 Vertical and horizontal wall components with dry joints 115

CB.4 Vertical and horizontal wall components with mortar joints 115

CC.1 Basis of temperature profiles 117

CC.2 Temperature profiles for AAC wall, floor and roof components 117

CC.3 Temperature profiles for AAC beams 119

CC.4 Calculation assumptions 127

Annex B (normative) Design by testing 84

Annex C (normative) Resistance to fire design of AAC components and structures 94

Annex CA (normative) Modulus of elasticity and maximum strain of AAC and reinforcing steel at
Annex CB (informative) Joints between AAC components satisfying resistance to fire E 114

Annex CC (normative) Temperature profiles of AAC wall, floor and roof components and AAC
beams 117

Annex CD (normative) Resistance to fire tabulated data for walls with mechanical impact 128

Annex D (informative) Recommended values for partial safety factors 130

D.1 General 130
D.2 Ultimate Limit States (ULS) 130
D.3 Serviceability Limit States (SLS) 131

prefabricated reinforced AAC components 132

E.1 Calculation of prestrain from test results 132
E.1.1 General 132
E.1.2 Symbols 133
E.1.3 Cross-section values of AAC components 133
E.1.4 Calculation of prestrain 0 from steel measurement 133
E.2 Cross-sectional analysis of a AAC component in SLS if prestress is taken into account 134
E.3 Splitting forces due to prestress 134
E.4 Methods to prevent end cracks due to prestress 135

F.1 Quality control 136

autoclaved aerated concrete under the EC Construction Product Directive 138

ZA.1 Clauses of this European Standard addressing the provisions of EC Construction Products
Directive 138

ZA.2 Procedures for the attestation of conformity of products 146

ZA.2.1 Systems of attestation of conformity 146

ZA.2.2 EC Certificate and Declaration of conformity 148

ZA.3 CE marking and labelling 149

ZA.3.1 General 149

ZA.3.2 Declaration of geometrical data and material properties 150

ZA.3.3 Declaration of product properties 153

ZA.3.4 Declaration of compliance with given design specification 155

ZA.3.5 Declaration of compliance with a given design specification 156

ZA.3.6 Simplified CE-marking label with reference to a manufacturer's catalogue 159

ZA.3.7 Additional information 160

Bibliography 161

Figures Figure 1 -- Determination of dry thermal conductivity 10dry 27

Figure A.1 -- Determination of effective span leff 52

Figure A.2 -- Bi-linear stress-strain diagram for AAC in compression for cross-sectional design 54

Figure A.3 -- Design stress-strain diagram for reinforcing steel 55

Figure A.4 -- Strain diagrams in the ultimate limit state 56

Figure A.5 -- Notation for components subjected to shear 59

Figure A.6 --Structural model and possible load cases for the modified model column method 64

Figure A.7 -- Relation between curvature and strain Two curvatures (great curvature and small curvature) are presented 67

Figure A.8 -- Application of punching provisions in non-standard cases 70

Figure A.9 -- Critical perimeter around loaded areas located away from an unsupported edge 70

Figure A.10 -- Critical perimeter near an opening 71

Figure A.11 -- Critical sections near unsupported edges 71

Figure A.12 -- Idealised box section 73

Figure A.13 -- Definition of the areas to be introduced in Equation (A.39) 74

Annex E (informative) Recommendations for the consideration of prestress in the design of Annex F (informative) Statistical methods for quality control 136

Annex ZA (informative) Provisions for the CE marking of prefabricated reinforced components of Figure A.14 -- Moment curvature relationship 79

Figure A.15 -- Effective length of transverse anchorage bars 82

Figure A.16 -- Envelope line for determining the tensile force in the longitudinal reinforcement 82

Figure A.17 -- Support length ao 83

Figure B.1 -- Definition of shear span ls 86

Figure B.2 -- Typical reinforcement layouts in AAC-components 86

Figure B.3 -- Diagram for determination of the column factor k 89

Figure B.4 -- N/M - interaction diagram of the cross-section representing the results of three test series 91

Figure B.5 -- Envelope line for determining the section of the actual bending moment, Mda 93

Figure C.1 - Coefficient kc() allowing for decrease of compressive strength, fck, of AAC at elevated temperature 100

Figure C.2 - Coefficient ks() allowing for decrease of characteristic strength fyk of tension and compression reinforcement 101

Figure C.3 - Sections of AAC components showing nominal axis distance a and nominal concrete cover c of reinforcement 103

Figure C.4- Reduction of strength and cross-section for sections exposed to fire 108

Figure C.5 - Division of a wall, with both sides exposed to fire, into zones for use in calculation of strength reduction and az values 108

Figure CA.1 -- Stress-strain relationship of AAC under compression at elevated temperature 111

Fisgure CA.2 -- Stress-strain relationship of reinforcing steel at elevated temperature 113

Figure CB.1 -- Example of a dry joint in structures made of floor or roof components with cover (e.g. topping) preventing movement of air through the joint 114

Figure CB.2 -- Examples of mortar joints in structures made of floor or roof components 114

Figure CB.3 -- Example of dry joints with two sealing strips in structures made of horizontal wall components 115

Figure CB.4 -- Examples of thin layer mortar joints in structures made of vertical or horizontal wall components 116

Figure CC.1 - Temperature profiles for AAC wall, floor and roof components with a dry density of 300 kg/m 117

Figure CC.2 - Temperature profiles for AAC wall, floor and roof components with a dry density of 400 kg/m 118

Figure CC.3 - Temperature profiles for AAC wall, floor and roof components with a dry density of 500 kg/m 118

Figure CC.4 - Temperature profiles for AAC wall, floor and roof components with a dry density of 600 kg/m 119

Figure CC.5 -- Temperature profiles of the non exposed face of component for the determination of the criteria of the classification to fire, for a dry density of 300 and 600 kg/m 120

Figure CC.6 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 300 kg/m , exposed on three sides to standard fire 120

Figure CC.7 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 400 kg/m , exposed on three sides to standard fire 121

Figure CC.8 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 500 kg/m , exposed on three sides to standard fire 122

Figure CC.9 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 600 kg/m , exposed on three sides to standard fire 122

Figure CC.10 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 300 kg/m , exposed on three sides to standard fire 123

Figure CC.11 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 400 kg/m , exposed on three sides to standard fire 124

Figure CC.12 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 500 kg/m , exposed on three sides to standard fire 125

Figure CC.13 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 600 kg/m , exposed on three sides to standard fire 126

Figure E.1 -- Analysis of prestress by means of an assumed external force 132

Figure ZA.1 - Example of CE marking with Method 1 152

Figure ZA.2 - Example of CE marking with Method 2 154

Figure ZA.3a - Example of CE marking with Method 3a 156

Figure ZA.3b - Example of CE marking with Method 3b 158

Figure ZA.4 -- Example of simplified label 159

Tables Table 1 -- Density classes 22

Table 2 -- Compressive strength classes for AAC 24

Table 3 -- Creep classes 26

Table 4 -- Dry thermal conductivity 10dry of AAC for 50 % and 90 % of production with a confidence level of = 90 % 28

Table 5 -- Welding strength classes and welding strength factors kW 29

Table 6 -- Bond classes 30

Table 7 -- Prestress classes 30

Table 8 -- Dimensional tolerances of components 33

Table 9 -- Final shrinkage strains 0 for AAC components 34

Table 10 -- Thickness classes of structural components 35

Table 11 -- Exposure classes and protective measures related to environmental conditions 38

Table 12 -- Initial type-testing of the AAC components 43

Table 13 -- Testing of the finished product; AAC components for structural uses 45

Table 14 -- Testing of the finished product; AAC components for non-structural uses 47

Table A.1 -- Bond Classes 81

Table B.1 -- Design loadbearing capacity Rcd of components 92

Table C.1 -- Thermal conductivity of AAC () at elevated temperature 100

Table C.2 -- Minimum wall thickness of non loadbearing AAC walls with a dry density between 350 kg/m and 700 kg/m 103

Table C.3a -- Minimum wall thickness and axis distance amin for separating loadbearing AAC walls. AAC dry density 350 kg/m to 700 kg/m and structural or non-structural reinforcement for resistance to fire REI 104

Table C.3b -- Minimum wall thickness and minimum axis distance amin for non separating loadbearing AAC walls supported on at least two opposite ends of the components. AAC dry density 350 kg/m to 700 kg/m³ and structural or non-structural reinforcement for resistance to fire R 104

Table C.4 -- Minimum dimensions (height hmin and width bmin) in mm and minimum axis distance amin in mm to the bottom side and to the vertical sides of AAC beams in relation to the maximum span length 104

Table C.5 -- Minimum thickness hmin in mm and minimum axis distance amin in mm of AAC floor and roof components in relation to maximum span length 105

Table C.6 -- Reduction of the dimensions of AAC cross-section from fire exposed surfaces 110

Table CA.1 --Values for the parameters of stress-strain relationship of AAC in compression at elevated temperature 111

Table CA.2 - Values for the parameters of stress-strain relationship of reinforcing steel at elevated temperature 112

Table CC.1 127

Table CC.2 127

Table CD.1 - Minimum wall thickness and minimum axis distance amin of AAC walls with mechanical impact supported on at least two opposite ends; AAC dry density 450 kg/m to 700 kg/m with structural or non structural reinforcement for resistance to fire REI-M and EI-M 128

Table CD.2 -- Minimum amount of reinforcement for AAC components used in walls with mechanical impact 129

Table D.1 -- Safety parameter for failure type 130

Table D.2 -- Safety parameter for accuracy when determining the material parameter 130

Table D.3 -- Safety parameters depending on variation 131

Table D.4 -- Partial safety factors 131

Table F.1 -- Control factor kn as a function of samples n with a fractile value of 5 % (p = 0,95) and a confidence level of 0,75 (using bayesian procedures with "vague" prior distribution) and under the assumption that the safety level (Annex D) is based on a summarised variation of VR = 0,10 137

Table F.2-- Coefficient ks as a function of samples n with a fractile value of 5 % (p = 0,95) and a confidence level 0,75 (using bayesian procedures with "vague" prior distribution) 137

Table ZA.1a -- Harmonised clauses for loadbearing wall components 139

Table ZA.1b -- Harmonised clauses for retaining wall components 140

Table ZA.1c -- Harmonised clauses for roof components 141

Table ZA.1d -- Harmonised clauses for floor components 142

Table ZA.1e -- Harmonised clauses for linear components 143

Table ZA.1f -- Harmonised clauses for non-loadbearing wall and noise barriers components 144

Table ZA.1g -- Harmonised clauses for cladding components 145

Table ZA.1h -- Harmonised clauses for small box culvert components 146

Table ZA.2a -- Systems of attestation of conformity 147

Table ZA.2b -- Assignation of evaluation of conformity tasks (for structural components) under system 2+ 1) 147

Table ZA.2c -- Assignation of evaluation of conformity tasks (for non structural or light structural components) under system 4 1) 148