

# DIN EN 12602:2008-08 (E)

## Prefabricated reinforced components of autoclaved aerated concrete

---

<b>Contents</b>		<b>Page</b>
Foreword .....		9
<b>1</b>	<b>Scope .....</b>	<b>11</b>
<b>2</b>	<b>Normative references .....</b>	<b>11</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviations .....</b>	<b>13</b>
3.1	Terms and definitions .....	13
3.2	Symbols .....	14
3.2.1	General symbols .....	14
3.2.2	Subscripts .....	14
3.2.3	Symbols used in this European Standard (including normative annexes, except Annex C) .....	15
3.3	Abbreviations .....	20
<b>4</b>	<b>Properties and requirements of materials .....</b>	<b>21</b>
4.1	Constituent materials of autoclaved aerated concrete .....	21
4.1.1	General .....	21
4.1.2	Release of dangerous substances .....	21
4.2	Autoclaved aerated concrete parameters .....	22
4.2.1	General .....	22
4.2.2	Dry density .....	22
4.2.3	Characteristic strength values .....	23
4.2.4	Compressive strength .....	23
4.2.5	Tensile strength and flexural strength .....	24
4.2.6	Stress-strain diagram .....	24
4.2.7	Modulus of elasticity .....	24
4.2.8	Poisson's ratio .....	25
4.2.9	Coefficient of thermal expansion .....	25
4.2.10	Drying shrinkage .....	25
4.2.11	Creep .....	25
4.2.12	Specific heat .....	26
4.2.13	Thermal conductivity .....	26
4.2.14	Water vapour permeability .....	28
4.2.15	Water tightness .....	28
4.3	Reinforcement .....	28
4.3.1	Steel .....	28
4.3.2	Structural reinforcement .....	28
4.3.3	Effective diameter of coated bars .....	29
4.3.4	Non-structural reinforcement .....	29
4.4	Bond .....	30
4.5	Thermal prestress .....	30
4.5.1	General .....	30
4.5.2	Declared mean initial prestrain $0m,g$ .....	31
<b>5</b>	<b>Properties and requirements of components .....</b>	<b>31</b>
5.1	General .....	31
5.1.1	Mechanical resistance .....	31
5.1.2	Acoustic properties .....	31
5.1.3	Reaction to fire and resistance to fire .....	32
5.1.4	Design thermal resistance and design thermal conductivity .....	32
5.2	Technical requirements and declared properties .....	32

5.2.1	Dimensions and tolerances .....	32
5.2.2	Mass of the components .....	33
5.2.3	Dimensional stability .....	33
5.2.4	Load-bearing capacity .....	34
5.2.5	Deflections .....	34
5.2.6	Joint strength .....	35
5.2.7	Minimum requirements .....	35
5.3	Durability .....	37
5.3.1	General .....	37
5.3.2	Environmental conditions .....	37
5.3.3	Corrosion protection of reinforcement .....	38
5.3.4	Freeze and thaw resistance .....	39
6	Evaluation of conformity .....	39
6.1	Introduction .....	39
6.2	Initial type-testing of the component .....	39
6.3	Factory production control .....	40
6.3.1	General .....	40
6.3.2	Process control .....	40
6.3.3	Finished products .....	41
6.4	Initial inspection of the factory and the factory production control .....	41
6.4.1	Information to be supplied .....	41
6.4.2	Inspection .....	41
6.4.3	Reports .....	41
6.5	Surveillance, assessment and acceptance of the factory production control .....	42
6.5.1	Inspection tasks .....	42
6.5.2	Frequency of inspections .....	42
6.5.3	Reports .....	42
6.6	Actions to be taken in the event of non-conformity .....	42
7	Basis for design .....	48
7.1	Design methods .....	48
7.2	Limit states .....	48
7.3	Actions .....	48
8	Marking, labelling and designation .....	49
8.1	Standard designation .....	49
8.2	Production detail information .....	49
8.3	Additional information on accompanying documents .....	49
A.1	General .....	51
A.2	Ultimate limit states (ULS) General design assumptions .....	51
A.3	Ultimate limit states (ULS): design for bending and combined bending and axial compression .....	53
A.3.1	Design assumptions .....	53
A.3.2	Stress-strain diagram for AAC .....	53
A.3.3	Stress-strain diagram for reinforcing steel .....	54
A.3.4	Minimum reinforcement .....	56
A.4	Shear .....	57
A.4.1	Shear design for components predominantly under transverse load .....	57
A.5	Ultimate limit states induced by structural deformation (buckling) .....	62
A.5.1	General .....	62
A.5.2	Method based on Euler formula .....	62
A.5.3	Modified model column method .....	63
A.6	Punching .....	69
A.6.1	General .....	69
A.6.2	Scope and definitions .....	69
A.6.3	Design method for punching shear .....	71
A.7	Primary torsion/combined primary torsion and shear .....	72
A.8	Concentrated forces .....	74
A.9	Serviceability limit states (SLS) .....	75
A.9.1	General .....	75

A.9.2	Limitation of stresses under serviceability conditions .....	75
A.9.3	Serviceability limit states of cracking .....	76
A.9.4	Serviceability limit states of deformation .....	76
A.10	Detailing of reinforcement .....	79
A.10.1	General .....	79
A.10.2	Bond .....	79
<b>Annex A (normative) Design by calculation .....</b>		<b>51</b>
A.10.3	Anchorage .....	80
A.11	Support length .....	82
B.1	General .....	84
B.2	Safety evaluation .....	85
B.2.1	General .....	85
B.2.2	Brittle and ductile failure .....	85
B.3	Ultimate limit state .....	85
B.3.1	General .....	85
B.3.2	Transversely loaded components .....	85
B.3.3	Longitudinally loaded components .....	87
B.3.4	Simultaneously transversely and longitudinally loaded wall components .....	90
B.3.5	Anchorage .....	91
B.4	Serviceability limit states .....	93
B.4.1	Crack width control .....	93
B.4.2	Deformations .....	93
C.1	General .....	94
C.1.1	Scope .....	94
C.1.2	Distinction between principles and application rules .....	94
C.1.3	Terms and definitions .....	94
C.1.4	Symbols .....	96
C.1.5	Units .....	97
C.2	Basic principles .....	97
C.2.1	Performance requirements .....	97
C.2.2	Design values of material properties .....	98
C.2.3	Assessment methods .....	98
C.3	Material properties .....	99
C.3.1	General .....	99
C.3.2	AAC .....	99
C.3.3	Steel .....	101
C.4	Structural fire design methods .....	102
C.4.1	General .....	102
C.4.2	Tabulated data .....	102
C.4.3	Simplified design methods .....	106
C.4.4	Anchorage .....	110
C.5	Protective layers .....	110
elevated temperature .....		111
CB.1	Floor and roof components with dry joints .....	114
CB.2	Floor and roof components with mortar joints .....	114
CB.3	Vertical and horizontal wall components with dry joints .....	115
CB.4	Vertical and horizontal wall components with mortar joints .....	115
CC.1	Basis of temperature profiles .....	117
CC.2	Temperature profiles for AAC wall, floor and roof components .....	117
CC.3	Temperature profiles for AAC beams .....	119

CC.4 Calculation assumptions .....	127
Annex B (normative) Design by testing .....	84
Annex C (normative) Resistance to fire design of AAC components and structures .....	94
Annex CA (normative) Modulus of elasticity and maximum strain of AAC and reinforcing steel at Annex CB (informative) Joints between AAC components satisfying resistance to fire E	114
Annex CC (normative) Temperature profiles of AAC wall, floor and roof components and AAC beams .....	117
Annex CD (normative) Resistance to fire tabulated data for walls with mechanical impact .....	128
Annex D (informative) Recommended values for partial safety factors .....	130
D.1 General .....	130
D.2 Ultimate Limit States (ULS) .....	130
D.3 Serviceability Limit States (SLS) .....	131
prefabricated reinforced AAC components .....	132
E.1 Calculation of prestrain from test results .....	132
E.1.1 General .....	132
E.1.2 Symbols .....	133
E.1.3 Cross-section values of AAC components .....	133
E.1.4 Calculation of prestrain 0 from steel measurement .....	133
E.2 Cross-sectional analysis of a AAC component in SLS if prestress is taken into account	134
E.3 Splitting forces due to prestress .....	134
E.4 Methods to prevent end cracks due to prestress .....	135
F.1 Quality control .....	136
autoclaved aerated concrete under the EC Construction Product Directive .....	138
ZA.1 Clauses of this European Standard addressing the provisions of EC Construction Products Directive .....	138
ZA.2 Procedures for the attestation of conformity of products .....	146
ZA.2.1 Systems of attestation of conformity .....	146
ZA.2.2 EC Certificate and Declaration of conformity .....	148
ZA.3 CE marking and labelling .....	149
ZA.3.1 General .....	149
ZA.3.2 Declaration of geometrical data and material properties .....	150
ZA.3.3 Declaration of product properties .....	153
ZA.3.4 Declaration of compliance with given design specification .....	155
ZA.3.5 Declaration of compliance with a given design specification .....	156
ZA.3.6 Simplified CE-marking label with reference to a manufacturer's catalogue .....	159
ZA.3.7 Additional information .....	160
Bibliography .....	161

Figures Figure 1 -- Determination of dry thermal conductivity $10_{dry}$ .....	27
Figure A.1 -- Determination of effective span $l_{eff}$ .....	52
Figure A.2 -- Bi-linear stress-strain diagram for AAC in compression for cross-sectional design .....	54
Figure A.3 -- Design stress-strain diagram for reinforcing steel .....	55
Figure A.4 -- Strain diagrams in the ultimate limit state .....	56
Figure A.5 -- Notation for components subjected to shear .....	59
Figure A.6 -- Structural model and possible load cases for the modified model column method .....	64
Figure A.7 -- Relation between curvature and strain Two curvatures (great curvature and small curvature) are presented .....	67
Figure A.8 -- Application of punching provisions in non-standard cases .....	70
Figure A.9 -- Critical perimeter around loaded areas located away from an unsupported edge .....	70
Figure A.10 -- Critical perimeter near an opening .....	71
Figure A.11 -- Critical sections near unsupported edges .....	71
Figure A.12 -- Idealised box section .....	73
Figure A.13 -- Definition of the areas to be introduced in Equation (A.39) .....	74
Annex E (informative) Recommendations for the consideration of prestress in the design of Annex F (informative) Statistical methods for quality control .....	136
Annex ZA (informative) Provisions for the CE marking of prefabricated reinforced components of Figure A.14 -- Moment curvature relationship .....	79
Figure A.15 -- Effective length of transverse anchorage bars .....	82
Figure A.16 -- Envelope line for determining the tensile force in the longitudinal reinforcement .....	82
Figure A.17 -- Support length $a_o$ .....	83
Figure B.1 -- Definition of shear span $l_s$ .....	86
Figure B.2 -- Typical reinforcement layouts in AAC-components .....	86
Figure B.3 -- Diagram for determination of the column factor $k$ .....	89
Figure B.4 -- N/M - interaction diagram of the cross-section representing the results of three test series .....	91
Figure B.5 -- Envelope line for determining the section of the actual bending moment, $M_{da}$ .....	93
Figure C.1 - Coefficient $k_c()$ allowing for decrease of compressive strength, $f_{ck}$ , of AAC at elevated temperature .....	100
Figure C.2 - Coefficient $k_s()$ allowing for decrease of characteristic strength $f_{yk}$ of tension and compression reinforcement .....	101
Figure C.3 - Sections of AAC components showing nominal axis distance $a$ and nominal concrete cover $c$ of reinforcement .....	103
Figure C.4- Reduction of strength and cross-section for sections exposed to fire .....	108

Figure C.5 - Division of a wall, with both sides exposed to fire, into zones for use in calculation of strength reduction and az values .....	108
Figure CA.1 -- Stress-strain relationship of AAC under compression at elevated temperature .....	111
Figure CA.2 -- Stress-strain relationship of reinforcing steel at elevated temperature .....	113
Figure CB.1 -- Example of a dry joint in structures made of floor or roof components with cover (e.g. topping) preventing movement of air through the joint .....	114
Figure CB.2 -- Examples of mortar joints in structures made of floor or roof components .....	114
Figure CB.3 -- Example of dry joints with two sealing strips in structures made of horizontal wall components .....	115
Figure CB.4 -- Examples of thin layer mortar joints in structures made of vertical or horizontal wall components .....	116
Figure CC.1 - Temperature profiles for AAC wall, floor and roof components with a dry density of 300 kg/m .....	117
Figure CC.2 - Temperature profiles for AAC wall, floor and roof components with a dry density of 400 kg/m .....	118
Figure CC.3 - Temperature profiles for AAC wall, floor and roof components with a dry density of 500 kg/m .....	118
Figure CC.4 - Temperature profiles for AAC wall, floor and roof components with a dry density of 600 kg/m .....	119
Figure CC.5 -- Temperature profiles of the non exposed face of component for the determination of the criteria of the classification to fire, for a dry density of 300 and 600 kg/m .....	120
Figure CC.6 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 300 kg/m , exposed on three sides to standard fire .....	120
Figure CC.7 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 400 kg/m , exposed on three sides to standard fire .....	121
Figure CC.8 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 500 kg/m , exposed on three sides to standard fire .....	122
Figure CC.9 - Temperature profiles in °C for AAC-beams (b x h = 150 mm x 200 mm) with a dry density of 600 kg/m , exposed on three sides to standard fire .....	122
Figure CC.10 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 300 kg/m , exposed on three sides to standard fire .....	123
Figure CC.11 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 400 kg/m , exposed on three sides to standard fire .....	124
Figure CC.12 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 500 kg/m , exposed on three sides to standard fire .....	125
Figure CC.13 - Temperature profiles in °C for AAC-beams (b x h = 300 mm x 400 mm) with a dry density of 600 kg/m , exposed on three sides to standard fire .....	126
Figure E.1 -- Analysis of prestress by means of an assumed external force .....	132
Figure ZA.1 - Example of CE marking with Method 1 .....	152

Figure ZA.2 - Example of CE marking with Method 2 .....	154
Figure ZA.3a - Example of CE marking with Method 3a .....	156
Figure ZA.3b - Example of CE marking with Method 3b .....	158
Figure ZA.4 -- Example of simplified label .....	159
Tables Table 1 -- Density classes .....	22
Table 2 -- Compressive strength classes for AAC .....	24
Table 3 -- Creep classes .....	26
Table 4 -- Dry thermal conductivity $10_{dry}$ of AAC for 50 % and 90 % of production with a confidence level of = 90 % .....	28
Table 5 -- Welding strength classes and welding strength factors $k_W$ .....	29
Table 6 -- Bond classes .....	30
Table 7 -- Prestress classes .....	30
Table 8 -- Dimensional tolerances of components .....	33
Table 9 -- Final shrinkage strains $\epsilon_0$ for AAC components .....	34
Table 10 -- Thickness classes of structural components .....	35
Table 11 -- Exposure classes and protective measures related to environmental conditions .....	38
Table 12 -- Initial type-testing of the AAC components .....	43
Table 13 -- Testing of the finished product; AAC components for structural uses .....	45
Table 14 -- Testing of the finished product; AAC components for non-structural uses .....	47
Table A.1 -- Bond Classes .....	81
Table B.1 -- Design loadbearing capacity $R_{cd}$ of components .....	92
Table C.1 -- Thermal conductivity of AAC ( $\lambda$ ) at elevated temperature .....	100
Table C.2 -- Minimum wall thickness of non loadbearing AAC walls with a dry density between 350 kg/m <sup>3</sup> and 700 kg/m <sup>3</sup> .....	103
Table C.3a -- Minimum wall thickness and axis distance $a_{min}$ for separating loadbearing AAC walls. AAC dry density 350 kg/m <sup>3</sup> to 700 kg/m <sup>3</sup> and structural or non-structural reinforcement for resistance to fire REI .....	104
Table C.3b -- Minimum wall thickness and minimum axis distance $a_{min}$ for non separating loadbearing AAC walls supported on at least two opposite ends of the components. AAC dry density 350 kg/m <sup>3</sup> to 700 kg/m <sup>3</sup> and structural or non-structural reinforcement for resistance to fire R .....	104
Table C.4 -- Minimum dimensions (height $h_{min}$ and width $b_{min}$ ) in mm and minimum axis distance $a_{min}$ in mm to the bottom side and to the vertical sides of AAC beams in relation to the maximum span length .....	104
Table C.5 -- Minimum thickness $h_{min}$ in mm and minimum axis distance $a_{min}$ in mm of AAC floor and roof components in relation to maximum span length .....	105

Table C.6 -- Reduction of the dimensions of AAC cross-section from fire exposed surfaces .....	110
Table CA.1 --Values for the parameters of stress-strain relationship of AAC in compression at elevated temperature .....	111
Table CA.2 - Values for the parameters of stress-strain relationship of reinforcing steel at elevated temperature .....	112
Table CC.1 .....	127
Table CC.2 .....	127
Table CD.1 - Minimum wall thickness and minimum axis distance $a_{min}$ of AAC walls with mechanical impact supported on at least two opposite ends; AAC dry density 450 kg/m to 700 kg/m with structural or non structural reinforcement for resistance to fire REI-M and EI-M .....	128
Table CD.2 -- Minimum amount of reinforcement for AAC components used in walls with mechanical impact .....	129
Table D.1 -- Safety parameter for failure type .....	130
Table D.2 -- Safety parameter for accuracy when determining the material parameter .....	130
Table D.3 -- Safety parameters depending on variation .....	131
Table D.4 -- Partial safety factors .....	131
Table F.1 -- Control factor $k_n$ as a function of samples $n$ with a fractile value of 5 % ( $p = 0,95$ ) and a confidence level of 0,75 (using bayesian procedures with "vague" prior distribution) and under the assumption that the safety level (Annex D) is based on a summarised variation of $VR = 0,10$ .....	137
Table F.2-- Coefficient $k_s$ as a function of samples $n$ with a fractile value of 5 % ( $p = 0,95$ ) and a confidence level 0,75 (using bayesian procedures with "vague" prior distribution) .....	137
Table ZA.1a -- Harmonised clauses for loadbearing wall components .....	139
Table ZA.1b -- Harmonised clauses for retaining wall components .....	140
Table ZA.1c -- Harmonised clauses for roof components .....	141
Table ZA.1d -- Harmonised clauses for floor components .....	142
Table ZA.1e -- Harmonised clauses for linear components .....	143
Table ZA.1f -- Harmonised clauses for non-loadbearing wall and noise barriers components .....	144
Table ZA.1g -- Harmonised clauses for cladding components .....	145
Table ZA.1h -- Harmonised clauses for small box culvert components .....	146
Table ZA.2a -- Systems of attestation of conformity .....	147
Table ZA.2b -- Assignment of evaluation of conformity tasks (for structural components) under system 2+ 1) .....	147
Table ZA.2c -- Assignment of evaluation of conformity tasks (for non structural or light structural components) under system 4 1) .....	148