

DIN EN 15715:2010-04 (E)

Thermal insulation products - Instructions for mounting and fixing for reaction to fire testing - Factory made products

Contents		Page
Foreword		5
1	Scope	9
2	Normative references	9
3	Terms, definitions and abbreviated terms	9
3.1	Terms and definitions	9
3.2	Abbreviated terms used in this European Standard	10
4	Principle	10
5	Instructions for mounting and fixing of test specimens	11
5.1	General	11
5.2	Product and installation parameters	11
5.3	Mounting and fixing	12
5.3.1	Ignitability, EN ISO 11925-2 Exposure to thermal attack	12
5.3.2	Single Burning Item (SBI), EN 13823	12
5.4	Validity of test results for product groups (Field of application)	18
6	Instructions for mounting and fixing of products in standardised assemblies simulating end-use application(s)	18
6.1	General	18
6.2	Product and installation parameters	19
6.3	Mounting and fixing	20
6.3.1	Ignitability, EN ISO 11925-2	20
6.3.2	Single Burning Item (SBI) (EN 13823)	20
6.4	Validity of test result for a product group (Field of application)	25
Annex A (normative)	Product specific details	26
A.1	General	26
A.2	Mineral wool (MW)	26
A.3	Expanded polystyrene (EPS)	34
A.4	Extruded polystyrene foam (XPS)	39
A.5	Polyurethane and polyisocyanurate (PUR/PIR)	44
A.6	Phenolic Foam (PF)	50
A.7	Cellular Glass (CG)	56
A.8	Wood Wool (WW)	63
A.9	Expanded perlite (EPB)	67
A.10	Expanded cork (ICB)	70
A.11	Wood fibre (WF)	73
A.12	Flexible elastomeric foam (FEF)	76
A.13	Calcium silicate (CS)	82
A.14	Polyethylene foam (PEF)	88
Bibliography		94
Tables	Table 1 -- Product parameters	11
	Table 2 -- Installation parameters	12

Table 3 -- Thermal insulation product parameters in standardised assemblies	19
Table 4 -- Installation parameters of standardised assemblies	19
Table 5 -- Standard test configurations of standardised assemblies	21
Table A.1 -- Product parameters for MW - flat products, when tested as placed on the market or in standard test configuration of assemblies	26
Table A.2 -- Installation parameters for MW - flat products, as placed on the market	29
Table A.3 -- Product parameters for MW - pipe insulation products, as placed on the market	30
Table A.4 -- Installation parameters for MW - pipe insulation products, as placed on the market	31
Table A.5 -- Installation parameters for MW - flat products in standard test configuration of assemblies, simulating end-use applications	32
Table A.6 -- Product parameters for EPS - flat products, when tested as placed on the market or in standard test configuration of assemblies	34
Table A.7 -- Installation parameters for EPS - flat products as placed on the market	35
Table A.8 -- Product parameters for EPS - pipe insulation products, as placed on the market	36
Table A.9 -- Installation parameters for EPS - pipe insulation products, as placed on the market	37
Table A.10 -- Installation parameters for EPS - flat products in standard test configuration of assemblies, simulating end-use applications	38
Table A.11 -- Product parameters for XPS - flat products when tested as placed on the market or in standard test configuration of assemblies	39
Table A.12-- Installation parameters for XPS - flat products as placed on the market	40
Table A.13 -- Product parameters for XPS - pipe insulation products, as placed on the market	41
Table A.14 -- Installation parameters for XPS - pipe insulation products, as placed on the market ...	42
Table A.15 -- Installation parameters for XPS - flat products in standard test configuration of assemblies, simulating end-use applications	43
Table A.16 -- Product parameters for PUR/PIR - flat products when tested as placed on the market or in standard test configuration of assemblies	44
Table A.17 -- Installation parameters for PUR/PIR - flat products, as placed on the market	45
Table A.18 -- Product parameters for PUR/PIR - pipe insulation products, as placed on the market .	46
Table A.19 -- Installation parameters for PUR/PIR - pipe insulation products, as placed on the market	47
Table A.20 -- Installation parameters for PUR/ PIR - flat products in standard test configuration of assemblies, simulating end-use applications	48
Table A.21 -- Product parameters for PF - flat products, when tested as placed on the market or in standard test configuration of assemblies	50
Table A.22 -- Installation parameters for PF - flat products, as placed on the market	51
Table A.23 -- Product parameters for PF - pipe insulation products, as placed on the market	52

Table A.24 -- Installation parameters for PF - pipe insulation products, as placed on the market	53
Table A.25 -- Installation parameters for PF - flat products in standard test configuration of assemblies, simulating end-use applications	54
Table A.26 -- Product parameters for CG - flat products when tested as placed on the market or in standard test configuration of assemblies	56
Table A.27 -- Installation parameters for CG - flat products, as placed on the market	58
Table A.28 -- Product parameters for CG - pipe insulation products a , as placed on the market	59
Table A.29 -- Installation parameters for CG- linear pipe thermal insulation	60
Table A.30-- Installation parameters for CG -- flat products, in standard test configuration of assemblies simulating end-use applications	61
Table A.31 -- Product parameters for WW -- flat products, when tested as placed on the market or in standard test configuration of assemblies	63
Table A.31 (continued)	64
Table A.32 -- Installation parameters WW -- flat products, as placed on the market	65
Table A.33 -- Installation parameters for WW - flat products in standard test configuration of assemblies simulating end-use applications	66
Table A.34 -- Product parameters for EPB - flat products, when tested as placed on the market or in standard test configuration of assemblies	67
Table A.35-- Installation parameters for EPB - flat products, as placed on the market	68
Table A.36-- Installation parameters for EPB - flat products in standard test configuration of assemblies simulating end-use applications	69
Table A.37 -- Product parameters for ICB flat products, when tested as placed on the market or in standard test configuration of assemblies	70
Table A. 38-- Installation parameters for ICB - flat products, as placed on the market	71
Table A.39 -- Installation parameters for ICB - flat products in standard test configuration of assemblies simulating end-use applications	72
Table A.40 -- Product parameters for WF - flat products, when tested as placed on the market or in standard test configuration of assemblies	73
Table A.41-- Installation parameters for WF - flat products, as placed on the market	74
Table A.42-- Installation parameters for WF - flat products, in standard test configuration of assemblies simulating end-use applications	75
Table A.43 -- Product parameters for FEF - flat products, when tested as placed on the market or in standard test configuration of assemblies	76
Table A.44 -- Installation parameters for FEF - flat products, as placed on the market	77
Table A.45 -- Product parameters for FEF - pipe insulation products, as placed on the market	78
Table A.46 -- Installation parameters for FEF - pipe insulation products, as placed on the market	79

Table A.47 -- Installation parameters for FEF - for flat products in standard test configuration of assemblies simulating end-use applications	80
Table A.48 -- Product parameters for CS - flat products when tested as placed on the market or in standard test configuration of assemblies	82
Table A.49 -- Installation Parameters for CS - flat products as placed on the market	83
Table A.50 - Product parameters for CS - pipe insulation products, as placed on the market	84
Table A.51 - Installation parameters for CS - pipe insulation products, as placed on the market	85
Table A.52 -- Installation parameters for CS - flat products in standard test configuration of assemblies simulating end-use applications	86
Table A.53 -- Product parameters for PEF, flat products when tested as placed on the market or in standard test configuration of assemblies	88
Table A.54 -- Installation parameters for PEF flat products, as placed on the market	89
Table A.55 -- Product parameters for PEF - pipe insulation products as placed on the market	90
Table A.56 -- Installation parameters for PEF - pipe insulation products as placed on the market	91
Table A.57 -- Installation parameters for PEF - for flat products in standard test configuration of assemblies simulating end-use applications	92
Figures Figure 1 -- Installation of specimen according to EN 13823	15
Figure 2 -- Principle of positioning of minimum mechanical fixings	16
Figure 3 -- Joint arrangement for a product tested uncovered (front view)	16
Figure 4 -- Schematic drawings of the mounting of the test specimens in the SBI in the case of 25 mm insulation thickness	17
Figure 5 -- Fixing corrugated steel sheet (New figure is being drawn)	24