

ISO 14696:2009-05 (E)

Reaction-to-fire tests - Determination of fire and thermal parameters of materials, products and assemblies using an intermediate-scale calorimeter (ICAL)

| Contents | | Page |
|---------------------|--|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions, symbols and units | 2 |
| 3.1 | Terms and definitions | 2 |
| 3.2 | Symbols and units | 3 |
| 4 | Principle | 5 |
| 5 | Apparatus | 5 |
| 5.1 | General | 5 |
| 5.2 | Radiant panel | 5 |
| 5.3 | Radiant panel constant irradiance controller | 6 |
| 5.4 | Specimen holder assembly components | 7 |
| 5.5 | Other major components | 7 |
| 6 | Significance and use | 10 |
| 7 | Test specimens | 11 |
| 7.1 | Size and preparation | 11 |
| 7.2 | Conditioning | 11 |
| 8 | Calibration of apparatus | 11 |
| 8.1 | General | 11 |
| 8.2 | Heat flux uniformity | 11 |
| 8.3 | Heat flux/distance relationship | 11 |
| 8.4 | Heat release | 12 |
| 8.5 | Mass loss | 13 |
| 8.6 | Smoke obscuration | 13 |
| 8.7 | Gas analysis | 13 |
| 8.8 | Heat flux meter | 13 |
| 9 | Test methods | 14 |
| 9.1 | Preparation | 14 |
| 9.2 | Procedure | 14 |
| 10 | Calculations | 15 |
| 11 | Test report | 15 |
| 11.1 | Descriptive information | 15 |
| 11.2 | Table of numerical results | 16 |
| 11.3 | Graphical results | 16 |
| 11.4 | Descriptive results | 16 |
| 12 | Test limitations | 17 |
| 13 | Hazards | 17 |
| 14 | Precision and bias | 17 |
| Annex A (normative) | Design of exhaust system | 40 |

| | |
|--|-----------|
| Annex B (normative) Instrumentation in exhaust duct | 41 |
| Annex C (informative) Considerations for heat release measurements | 44 |
| Annex D (normative) Measurement equations | 48 |
| Annex E (informative) Commentary | 51 |
| Annex F (informative) Measurement and determination of other parameters and values needed in computer fire models | 53 |
| Annex G (informative) Determination of the precision and bias of the test method | 56 |
| Bibliography | 58 |