

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| Foreword .....   |  | iv          |
| Introduction .....   |  | v           |
| <b>1</b>   | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>   | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>   | <b>Terms, definitions, symbols and abbreviated terms .....</b>   | <b>2</b>    |
| <b>3.1</b>   | <b>Terms and definitions .....</b>   | <b>2</b>    |
| <b>3.2</b>   | <b>Symbols and abbreviated terms .....</b>   | <b>6</b>    |
| <b>4</b>   | <b>Equipment .....</b>   | <b>6</b>    |
| <b>4.1</b>   | <b>Cone penetrometer load sensors .....</b>  | <b>6</b>    |
| <b>4.2</b>   | <b>Tolerances .....</b>  | <b>6</b>    |
| <b>4.3</b>   | <b>Surface roughness .....</b>   | <b>7</b>    |
| <b>4.4</b>   | <b>Cone penetrometer .....</b>   | <b>7</b>    |
| <b>4.5</b>   | <b>Cone .....</b>  | <b>8</b>    |
| <b>4.6</b>   | <b>Friction sleeve .....</b>   | <b>9</b>    |
| <b>4.7</b>   | <b>Push rods .....</b>   | <b>11</b>   |
| <b>4.8</b>   | <b>Inner rods .....</b>  | <b>11</b>   |
| <b>4.9</b>   | <b>Measuring system .....</b>  | <b>11</b>   |
| <b>4.10</b>  | <b>Thrust machine .....</b>  | <b>12</b>   |
| <b>5</b>   | <b>Test procedures .....</b>   | <b>12</b>   |
| <b>5.1</b>   | <b>Selection of type of cone penetrometer test .....</b>   | <b>12</b>   |
| <b>5.2</b>   | <b>Selection of equipment and procedures .....</b>   | <b>13</b>   |
| <b>5.3</b>   | <b>Position and level of thrust machine .....</b>  | <b>15</b>   |
| <b>5.4</b>   | <b>Preparation .....</b>   | <b>15</b>   |
| <b>5.5</b>   | <b>Pushing of the cone penetrometer .....</b>  | <b>15</b>   |
| <b>5.6</b>   | <b>Use of friction reducer .....</b>   | <b>15</b>   |
| <b>5.7</b>   | <b>Frequency of logging parameters .....</b>   | <b>15</b>   |
| <b>5.8</b>   | <b>Measurement of cone penetration force for discontinuous penetration testing .....</b>               | <b>15</b>   |
| <b>5.9</b>   | <b>Measurement of cone penetration force for continuous testing .....</b>                              | <b>16</b>   |
| <b>5.10</b>  | <b>Measurement of sleeve friction force for discontinuous testing with M2 cone penetrometers .....</b> | <b>16</b>   |
| <b>5.11</b>  | <b>Measurement of total penetration force for discontinuous testing .....</b>                          | <b>16</b>   |
| <b>5.12</b>  | <b>Measurement of total penetration force for continuous testing (TM4) .....</b>                       | <b>16</b>   |
| <b>5.13</b>  | <b>Measurement of the penetration length .....</b>   | <b>16</b>   |
| <b>5.14</b>  | <b>Test completion .....</b>   | <b>16</b>   |
| <b>5.15</b>  | <b>Equipment checks and calibrations .....</b>   | <b>17</b>   |
| <b>6</b>   | <b>Test results .....</b>  | <b>17</b>   |
| <b>6.1</b>   | <b>Measured parameters .....</b>   | <b>17</b>   |
| <b>6.2</b>   | <b>Calculated parameters .....</b>   | <b>17</b>   |
| <b>7</b>   | <b>Reporting .....</b>   | <b>17</b>   |
| <b>7.1</b>   | <b>General .....</b>   | <b>17</b>   |
| <b>7.2</b>   | <b>Reporting of test results .....</b>   | <b>17</b>   |
| <b>7.3</b>   | <b>Presentation of test results .....</b>  | <b>20</b>   |
| <b>Annex A (normative) Maintenance, checks and calibration .....</b> |  | <b>21</b>   |
| <b>Bibliography .....</b>  |  | <b>23</b>   |