DIN EN 1366-5:2010-06 (E)

Fire resistance tests for service installations - Part 5: Service ducts and shafts

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Test equipment 7
4.1 General 7
4.2 Furnace 7
4.3 Loading equipment 7
4.4 Gas extraction equipment (optional) 7

5 Test conditions 7
5.1 Furnace 7
5.2 Loading 7

6 Test specimen 8
6.1 Size 8
6.1.1 General 8
6.1.2 Length 8
6.1.3 Cross-section 8
6.2 Number 8
6.3 Design 8
6.3.1 General 8
6.3.2 Duct and shaft arrangement 9

7 Installation of test specimen 10
7.1 General 10
7.2 Standard supporting construction 10
7.3 Non-standard supporting constructions 10

8 Conditioning 11
8.1 General 11
8.2 Sealing materials prepared with moisture 11

9 Application of instrumentation 11
9.1 Thermocouples 11
9.1.1 Furnace thermocouples (plate thermometers) 11
9.1.2 Thermocouple locations 11
9.2 Pressure 12

10 Test procedure 12
10.1 General 12
10.2 Test measurements and observations 12
10.2.1 General 12
10.2.2 Integrity 12
10.2.3 Insulation (temperature of the surfaces outside the furnace - for both exposure at the inside and exposure at the outside) 13

10.2.4 Additional observations 13
10.3 Termination of the test 13

11 Performance criteria 13
11.1 Integrity 13
11.2 Insulation 13

12 Test report 13

13 Field of direct application of test results 14
13.1 Walls or floors through which the ducts or shafts lead 14
13.2 Sizes of ducts or shafts 14
13.2.1 Fire exposure from outside 14
13.2.2 Fire exposure from inside 15
13.3 Admissible services 15
13.4 Suspension devices for ducts 15
13.4.1 Material and sizing 15
13.4.2 Elongation 15

Bibliography 24