

DIN EN 1366-5:2010-06 (E)

Fire resistance tests for service installations - Part 5: Service ducts and shafts

Contents		Page
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Test equipment	7
4.1	General	7
4.2	Furnace	7
4.3	Loading equipment	7
4.4	Gas extraction equipment (optional)	7
5	Test conditions	7
5.1	Furnace	7
5.2	Loading	7
6	Test specimen	8
6.1	Size	8
6.1.1	General	8
6.1.2	Length	8
6.1.3	Cross-section	8
6.2	Number	8
6.3	Design	8
6.3.1	General	8
6.3.2	Duct and shaft arrangement	9
7	Installation of test specimen	10
7.1	General	10
7.2	Standard supporting construction	10
7.3	Non-standard supporting constructions	10
8	Conditioning	11
8.1	General	11
8.2	Sealing materials prepared with moisture	11
9	Application of instrumentation	11
9.1	Thermocouples	11
9.1.1	Furnace thermocouples (plate thermometers)	11
9.1.2	Thermocouple locations	11
9.2	Pressure	12
10	Test procedure	12
10.1	General	12
10.2	Test measurements and observations	12
10.2.1	General	12
10.2.2	Integrity	12
10.2.3	Insulation (temperature of the surfaces outside the furnace - for both exposure at the inside and exposure at the outside)	13

10.2.4	Additional observations	13
10.3	Termination of the test	13
11	Performance criteria	13
11.1	Integrity	13
11.2	Insulation	13
12	Test report	13
13	Field of direct application of test results	14
13.1	Walls or floors through which the ducts or shafts lead	14
13.2	Sizes of ducts or shafts	14
13.2.1	Fire exposure from outside	14
13.2.2	Fire exposure from inside	15
13.3	Admissible services	15
13.4	Suspension devices for ducts	15
13.4.1	Material and sizing	15
13.4.2	Elongation	15
	Bibliography	24