

DIN EN 1366-5:2010-06 (E)

Fire resistance tests for service installations - Part 5: Service ducts and shafts

Contents		Page
Foreword		4
Introduction		5
1 Scope		6
2 Normative references		6
3 Terms and definitions		6
4 Test equipment		7
4.1 General		7
4.2 Furnace		7
4.3 Loading equipment		7
4.4 Gas extraction equipment (optional)		7
5 Test conditions		7
5.1 Furnace		7
5.2 Loading		7
6 Test specimen		8
6.1 Size		8
6.1.1 General		8
6.1.2 Length		8
6.1.3 Cross-section		8
6.2 Number		8
6.3 Design		8
6.3.1 General		8
6.3.2 Duct and shaft arrangement		9
7 Installation of test specimen		10
7.1 General		10
7.2 Standard supporting construction		10
7.3 Non-standard supporting constructions		10
8 Conditioning		11
8.1 General		11
8.2 Sealing materials prepared with moisture		11
9 Application of instrumentation		11
9.1 Thermocouples		11
9.1.1 Furnace thermocouples (plate thermometers)		11
9.1.2 Thermocouple locations		11
9.2 Pressure		12
10 Test procedure		12
10.1 General		12
10.2 Test measurements and observations		12
10.2.1 General		12
10.2.2 Integrity		12
10.2.3 Insulation (temperature of the surfaces outside the furnace - for both exposure at the inside and exposure at the outside)		13

10.2.4	Additional observations	13
10.3	Termination of the test	13
11	Performance criteria	13
11.1	Integrity	13
11.2	Insulation	13
12	Test report	13
13	Field of direct application of test results	14
13.1	Walls or floors through which the ducts or shafts lead	14
13.2	Sizes of ducts or shafts	14
13.2.1	Fire exposure from outside	14
13.2.2	Fire exposure from inside	15
13.3	Admissible services	15
13.4	Suspension devices for ducts	15
13.4.1	Material and sizing	15
13.4.2	Elongation	15
Bibliography		24