

DIN EN 1991-1-4/NA:2010-12 (E)

National Annex - Nationally determined parameters - Eurocode 1: Actions on structures - Part 1-4: General actions - Wind actions

Contents	Page
Foreword	4
NA.1 Scope	5
NA.2.1 General	5
NA.2.2 National provisions	6
1 General	6
1.1 Scope	6
1.2 Normative references	6
1.5 Design assisted by testing and measurements	6
4 Wind velocity and velocity pressure	6
4.1 Basis for calculation	6
4.2 Basic values	7
4.3 Mean wind	7
4.4 Wind turbulence	8
4.5 Peak velocity pressure	8
5 Wind actions	9
5.3 Wind forces	9
6 Structural factor c_{scd}	9
6.1 General	9
6.3 Detailed procedure	9
7 Pressure and force coefficients	9
7.1 General	9
7.2 Pressure coefficients for buildings	10
7.4 Free-standing walls, parapets, fences and signboards	11
7.6 Structural elements with rectangular sections	11
7.7 Structural elements with sharp edged section	12
7.8 Structural elements with regular polygonal section	14
7.10 Spheres	14
7.11 Lattice structures and scaffoldings	14
7.13 Effective slenderness and end-effect factor	14
8 Wind actions on bridges	14
8.1 General	14
8.2 Choice of the response calculation procedure	15
8.3 Force coefficients	15
8.4 Bridge piers	15
Annex A (informative) Terrain effects	15
Annex B (informative) Procedure 1 for determining the structural factor c_{scd}	16
Annex C (informative) Procedure 2 for determining the structural factor c_{scd}	16
Annex D (informative) c_{scd} values for different types of structures	16

Annex E (informative) Vortex shedding and aeroelastic instabilities	16
Annex F (informative) Dynamic characteristics of structures	16
NCI Annex NA.A (normative) Wind zone map	17
NA.A.1 General	17
NA.A.2 Influence of the altitude	17
NCI Annex NA.B (normative) Influence of terrain roughness, orography and temporary states on the wind actions	18
NA.B.1 Specification of the terrain categories	18
NA.B.2 Transitions between the terrain categories	19
NA.B.3 Gust velocity pressure for buildings and structural elements not susceptible to vibrations .	20
NA.B.3.1 Procedures for determining the gust velocity pressure	20
NA.B.3.2 Simplified gust velocity pressure assumptions for buildings with heights of up to 25 m above ground level	20
NA.B.3.3 Height-dependent gust velocity pressure for the normal case	21
NA.B.4 Influence of orography	23
NA.B.4.1 Determining the influence of orography	23
NA.B.4.2 Numerical calculation of the orography coefficients	23
NA.B.5 Reduction of the velocity pressure for temporary states	23
NCI Annex NA.C (normative) Determination of the structural factor and evaluation of the vibration susceptibility	25
NA.C.1 Determination of the structural factor	25
NA.C.1.1 General	25
NA.C.1.2 Wind turbulence	26
NA.C.1.3 Structural factor c_{scd}	28
NA.C.1.4 Number of loads for dynamic response	28
NA.C.1.5 Service displacement and accelerations for serviceability assessments of a vertical structure	29
NA.C.2 Criterion for the susceptibility to vibrations	29
NCI Annex NA.D (normative) Vortex shedding	31
NCI Annex NA.E (informative) Aeroelastic instabilities	32
NA.E.1 Galloping and interference galloping	32
NA.E.2 Divergence and flutter	32
NA.E.2.1 General	32

NA.E.2.2 Divergence velocity	32
NDP Annex NA.F (normative) Dynamic characteristics of structures	35
NCI Annex NA.N (informative) Wind actions on bridges	36
NA.N.1 General	36
NA.N.2 Wind actions to be taken into account	36
NCI Annex NA.V (normative) Pressure coefficients for canopies	43
NCI Bibliography	45