DIN EN 15882-1:2012-03 (E)

Extended application of results from fire resistance tests for service installations - Part 1: Ducts

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Critical parameters and factors 6
4.1 General 6
4.2 Common thermal and mechanical parameters and factors 6
4.3 Common constructional parameters and factors 7
4.4 Specific constructional parameters and factors 7

5 Methodology 8

6 Requirements, performance criteria and influences 13
6.1 Requirements and performance criteria 13
6.2 Influences 13
6.2.1 Insulation 13
6.2.2 Integrity and leakage 13

7 Assessment scheme 14
7.1 General 14
7.2 Requirement for additional tests 14

8 Test arrangements and criteria for additional tests 14
8.1 Maximum dimensions of ducts which can be classified 14
8.2 Closed ducts with pressure differential 14
8.3 Open horizontal duct B 15
8.4 Open vertical duct B 15

9 Evaluation of fire resistance 15
9.1 Application of the basic and additional test results 15
9.2 Suspension devices 16
9.2.1 General 16
9.2.2 Dimensioning of suspension devices 16
9.2.3 Fixing of suspension devices 16
9.2.4 Longitudinal limit of suspension devices 17
9.3 Inspection openings/access panels 17
9.4 Components within ducts 17
9.5 Surface finishes 17
9.6 Change in wall or floor thickness 17

10 Extended application report 18

Bibliography 23