

DIN EN 846-14:2012-11 (E)

Methods of test for ancillary components for masonry - Part 14: Determination of the initial shear strength between the prefabricated part of a composite lintel and the masonry above it

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Principle	4
4	Terms, definitions and symbols	5
4.1	Terms and definitions	5
4.2	Symbols	5
5	Materials	6
5.1	Masonry units	6
5.1.1	Conditioning of the units	6
5.1.2	Testing	6
5.2	Mortar	6
5.3	Prefabricated part of the composite lintel	6
6	Apparatus	6
7	Preparation and curing of specimens	7
7.1	Preparation of masonry specimen	7
7.2	Curing and conditioning of the specimens	8
8	Procedure	8
8.1	Placing the specimens in the testing machine	8
8.2	Loading	10
8.2.1	Procedure A	10
8.2.2	Procedure B	10
8.2.3	Loading rate	10
8.3	Measurements and observations	11
8.4	Replications	11
9	Calculations	11
10	Evaluation of results	12
10.1	Procedure A	12
10.2	Procedure B	12
10.2.1	General	12
10.2.2	Simple method	12
10.2.3	Statistical method	13
11	Test report	14
Annex A (informative) Types of failure		15
Bibliography		17