

DIN EN 1745:2012-07 (E)

Masonry and masonry products - Methods for determining thermal properties

Contents		Page
Foreword		4
Introduction		5
1	Scope	7
2	Normative references	7
3	Terms, definitions and symbols	7
3.1	Terms and definitions	7
3.2	Symbols	9
3.3	Subscripts	10
4	Procedures to determine $\lambda_{10,dry}$, unit-values for solid masonry units and $\lambda_{10,dry,mor}$- values for mortars	11
4.1	General	11
4.2	$\lambda_{10,dry}$, mat-values for solid masonry units and mortars	11
4.2.1	Model S1. Determination of $\lambda_{10,dry}$,unit-values from tabulated $\lambda_{10,dry,mat}$ /net dry density relation	11
4.2.2	Model S2. Determination of $\lambda_{10,dry}$,unit-values based on $\lambda_{10,dry,mat}$ /net dry density curve	11
4.2.3	Model S3. Procedures to determine $\lambda_{10,dry}$,unit-values from determining the thermal transmittance (U_{mas}) of masonry built from solid masonry units and mortar	13
4.3	Test methods and numbers of samples to be taken for the different models	14
5	Procedures to determine equivalent $\lambda_{10,dry}$,unit-values for masonry units with formed voids and composite masonry units	14
5.1	General	14
5.2	Calculation methods	15
5.3	$\lambda_{10,dry}$,unit-values of masonry units	15
5.3.1	Determination of $\lambda_{10,dry}$,unit-values from tabulated unit /mat relation	15
5.3.2	Determination of $\lambda_{10,dry}$,unit-values based on calculation	16
5.3.3	Model P5. Determination of $\lambda_{10,dry}$,unit-values from determining the thermal transmittance (U_{mas}) of masonry built from masonry units with formed voids or composite masonry units and mortar	16
5.4	Test methods and numbers of samples to be taken for the different models	19
6	Moisture conversion	19
7	Procedures to determine design thermal values ($R_{design,mas}$ or design, mas) for masonry built from masonry units and mortar	20
7.1	General	20
7.2	$R_{design,mas}$- or design,mas-values based on calculation	20
7.3	$R_{design,mas}$- or design,mas-values of masonry built from masonry units with formed voids or composite masonry units and mortar based on tabulated values	21
7.3.1	Tabulated values	21
8.	Determination of the thermal transmittance of masonry	23
9.	Specific heat capacity	23
10.	Rounding rules for λ-values for masonry	23

Annex A (normative) Tabulated 10,dry,mat-values of materials used for masonry products	24
Annex B (informative) Rdry,mas- or 10,dry,mas-values of masonry built from a range of masonry units containing formed voids	35
Annex C (informative) Example of how to use the tables in Annex B	62
Annex D (normative) Requirements for appropriate calculation procedures	64
D.1 Capabilities of the program	64
D.2 Input data and results	64
D.3 Testing of the program accuracy	65
D.4 Reference cases	65
Annex E (informative) Evaluation of conformity	73
Annex F (informative) Alternative procedure for the moisture correction of units with formed voids	75
Bibliography	76