

# DIN EN 13024-1:2012-02 (E)

## Glass in building - Thermally toughened borosilicate safety glass - Part 1: Definition and description

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
Introduction .....		5
1	Scope .....	6
2	Normative references .....	6
3	Terms and definitions .....	6
4	Glass products .....	7
5	Fracture characteristics .....	8
6	Dimensions and tolerances .....	8
6.1	Nominal thickness and thickness tolerances .....	8
6.2	Width and length (sizes) .....	9
6.2.1	General .....	9
6.2.2	Maximum and minimum sizes .....	9
6.2.3	Tolerances and squareness .....	9
6.2.4	Edge deformation produced by the vertical process .....	10
6.3	Flatness .....	10
6.3.1	General .....	10
6.3.2	Measurement of overall bow .....	13
6.3.3	Measurement of roller wave .....	14
6.3.4	Measurement of edge lift (for horizontally toughened only) .....	15
6.3.5	Measurement of local distortion (for vertically toughened glass only) .....	16
6.3.6	Limitation on overall bow, roller waves and edge lift for horizontally toughened glass .....	17
6.3.7	Limitation on overall bow and local distortion for vertically toughened glass .....	17
6.3.8	Other distortions .....	17
7	Edge and/or surface work, holes, notches and cut-outs .....	18
7.1	Warning .....	18
7.2	Edge working of glass for toughening .....	18
7.3	Profiled edges .....	19
7.4	Round holes .....	19
7.4.1	General .....	19
7.4.2	Diameter of holes .....	19
7.4.3	Limitations on position of holes .....	19
7.4.4	Tolerances on hole diameters .....	20
7.4.5	Tolerances on position of holes .....	21
7.5	Holes/others .....	21
7.6	Notches and cut-outs .....	22
7.7	Shaped panes .....	22
8	Fragmentation test .....	22
8.1	General .....	22
8.2	Dimensions and number of test specimens .....	22
8.3	Test procedure .....	22
8.4	Assessment of fragmentation .....	23
8.5	Minimum values from the particle count .....	24

8.6	Selection of the longest particle .....	25
8.7	Maximum length of longest particle .....	25
9	Other physical characteristics .....	25
9.1	Optical distortion .....	25
9.1.1	Thermally toughened borosilicate safety glass produced by vertical toughening .....	25
9.1.2	Thermally toughened borosilicate safety glass produced by horizontal toughening .....	25
9.2	Anisotropy (iridescence) .....	25
9.3	Thermal durability .....	25
9.4	Mechanical strength .....	26
9.5	Classification of performance under accidental human impact .....	26
10	Marking .....	26
Annex A (informative) Curved thermally toughened borosilicate safety glass .....		27
Annex B (informative) Alternative method for the measurement of roller wave distortion .....		28
B.1	Apparatus .....	28
B.2	Method .....	28
B.3	Limitations .....	29
B.4	Alternative use of apparatus .....	29
Annex C (informative) Example of particle count .....		30
Bibliography .....		33