DIN EN 13024-1:2012-02 (E)

Glass in building - Thermally toughened borosilicate safety glass - Part 1: Definition and description

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Glass products 7

5 Fracture characteristics 8

6 Dimensions and tolerances 8
6.1 Nominal thickness and thickness tolerances 8
6.2 Width and length (sizes) 9
6.2.1 General 9
6.2.2 Maximum and minimum sizes 9
6.2.3 Tolerances and squareness 9
6.2.4 Edge deformation produced by the vertical process 10
6.3 Flatness 10
6.3.1 General 10
6.3.2 Measurement of overall bow 13
6.3.3 Measurement of roller wave 14
6.3.4 Measurement of edge lift (for horizontally toughened only) 15
6.3.5 Measurement of local distortion (for vertically toughened glass only) 16
6.3.6 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 17
6.3.7 Limitation on overall bow and local distortion for vertically toughened glass 17
6.3.8 Other distortions 17

7 Edge and/or surface work, holes, notches and cut-outs 18
7.1 Warning 18
7.2 Edge working of glass for toughening 18
7.3 Profiled edges 19
7.4 Round holes 19
7.4.1 General 19
7.4.2 Diameter of holes 19
7.4.3 Limitations on position of holes 19
7.4.4 Tolerances on hole diameters 20
7.4.5 Tolerances on position of holes 21
7.5 Holes/others 21
7.6 Notches and cut-outs 22
7.7 Shaped panes 22

8 Fragmentation test 22
8.1 General 22
8.2 Dimensions and number of test specimens 22
8.3 Test procedure 22
8.4 Assessment of fragmentation 23
8.5 Minimum values from the particle count 24

8.6 Selection of the longest particle 25
8.7 Maximum length of longest particle 25

9 Other physical characteristics 25
9.1 Optical distortion 25
9.1.1 Thermally toughened borosilicate safety glass produced by vertical toughening 25
9.1.2 Thermally toughened borosilicate safety glass produced by horizontal toughening 25
9.2 Anisotropy (iridescence) 25
9.3 Thermal durability 25
9.4 Mechanical strength 26
9.5 Classification of performance under accidental human impact 26

10 Marking 26

Annex A (informative) Curved thermally toughened borosilicate safety glass 27

Annex B (informative) Alternative method for the measurement of roller wave distortion 28

B.1 Apparatus 28
B.2 Method 28
B.3 Limitations 29
B.4 Alternative use of apparatus 29

Annex C (informative) Example of particle count 30

Bibliography 33