

DIN EN 13024-1:2012-02 (E)

Glass in building - Thermally toughened borosilicate safety glass - Part 1: Definition and description

Contents		Page
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Glass products	7
5	Fracture characteristics	8
6	Dimensions and tolerances	8
6.1	Nominal thickness and thickness tolerances	8
6.2	Width and length (sizes)	9
6.2.1	General	9
6.2.2	Maximum and minimum sizes	9
6.2.3	Tolerances and squareness	9
6.2.4	Edge deformation produced by the vertical process	10
6.3	Flatness	10
6.3.1	General	10
6.3.2	Measurement of overall bow	13
6.3.3	Measurement of roller wave	14
6.3.4	Measurement of edge lift (for horizontally toughened only)	15
6.3.5	Measurement of local distortion (for vertically toughened glass only)	16
6.3.6	Limitation on overall bow, roller waves and edge lift for horizontally toughened glass	17
6.3.7	Limitation on overall bow and local distortion for vertically toughened glass	17
6.3.8	Other distortions	17
7	Edge and/or surface work, holes, notches and cut-outs	18
7.1	Warning	18
7.2	Edge working of glass for toughening	18
7.3	Profiled edges	19
7.4	Round holes	19
7.4.1	General	19
7.4.2	Diameter of holes	19
7.4.3	Limitations on position of holes	19
7.4.4	Tolerances on hole diameters	20
7.4.5	Tolerances on position of holes	21
7.5	Holes/others	21
7.6	Notches and cut-outs	22
7.7	Shaped panes	22
8	Fragmentation test	22
8.1	General	22
8.2	Dimensions and number of test specimens	22
8.3	Test procedure	22
8.4	Assessment of fragmentation	23
8.5	Minimum values from the particle count	24

8.6	Selection of the longest particle	25
8.7	Maximum length of longest particle	25
9	Other physical characteristics	25
9.1	Optical distortion	25
9.1.1	Thermally toughened borosilicate safety glass produced by vertical toughening	25
9.1.2	Thermally toughened borosilicate safety glass produced by horizontal toughening	25
9.2	Anisotropy (iridescence)	25
9.3	Thermal durability	25
9.4	Mechanical strength	26
9.5	Classification of performance under accidental human impact	26
10	Marking	26
Annex A (informative) Curved thermally toughened borosilicate safety glass		27
Annex B (informative) Alternative method for the measurement of roller wave distortion		28
B.1	Apparatus	28
B.2	Method	28
B.3	Limitations	29
B.4	Alternative use of apparatus	29
Annex C (informative) Example of particle count		30
Bibliography		33