

DIN EN 1863-1:2012-02 (E)

Glass in building - Heat strengthened soda lime silicate glass - Part 1: Definition and description

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Glass products | 7 |
| 5 | Fracture characteristics | 8 |
| 6 | Dimensions and tolerances | 8 |
| 6.1 | Nominal thickness and thickness tolerances | 8 |
| 6.2 | Width and length (sizes) | 9 |
| 6.2.1 | General | 9 |
| 6.2.2 | Maximum and minimum sizes | 9 |
| 6.2.3 | Tolerances and squareness | 9 |
| 6.2.4 | Edge deformation produced by the vertical process | 10 |
| 6.3 | Flatness | 10 |
| 6.3.1 | General | 10 |
| 6.3.2 | Measurement of overall bow | 13 |
| 6.3.3 | Measurement of roller wave | 14 |
| 6.3.4 | Measurement of edge lift (for horizontally heat strengthened glass only) | 15 |
| 6.3.5 | Measurement of local distortion (for vertically heat strengthened glass only) | 16 |
| 6.3.6 | Limitation on overall bow, roller waves and edge lift for horizontally heat strengthened glass | 17 |
| 6.3.7 | Limitation on overall bow and local distortion for vertically heat strengthened glass | 18 |
| 6.3.8 | Other distortions | 18 |
| 7 | Edge and/or surface work, holes, notches and cut-outs | 18 |
| 7.1 | Warning | 18 |
| 7.2 | Edge working of glass for toughening | 18 |
| 7.3 | Profiled edges | 19 |
| 7.4 | Round holes | 19 |
| 7.4.1 | General | 19 |
| 7.4.2 | Diameter of holes | 20 |
| 7.4.3 | Limitations on position of holes | 20 |
| 7.4.4 | Tolerances on hole diameters | 21 |
| 7.4.5 | Tolerances on position of holes | 21 |
| 7.5 | Holes/others | 22 |
| 7.6 | Notches and cut-outs | 22 |
| 7.7 | Shaped panes | 23 |
| 8 | Fragmentation test | 23 |
| 8.1 | General | 23 |
| 8.2 | Dimensions and number of test specimens | 23 |
| 8.3 | Test procedure | 23 |
| 8.4 | Assessment of fragmentation | 24 |

| | | |
|--|--|----|
| 8.5 | Evaluation of fragmentation | 26 |
| 9 | Other physical characteristics | 26 |
| 9.1 | Optical distortion | 26 |
| 9.1.1 | Heat strengthened soda lime silicate glass produced by vertical toughening | 26 |
| 9.1.2 | Heat strengthened soda lime silicate glass produced by horizontal toughening | 27 |
| 9.2 | Anisotropy (iridescence) | 27 |
| 9.3 | Thermal durability | 27 |
| 9.4 | Mechanical strength | 27 |
| 10 | Marking | 28 |
| Annex A (informative) Alternative method for the measurement of roller wave distortion | | 29 |
| A.1 | Apparatus | 29 |
| A.2 | Method | 29 |
| A.3 | Limitations | 30 |
| A.4 | Alternative use of apparatus | 30 |