

ISO 28278-1:2011-12 (E)

Glass in building - Glass products for structural sealant glazing - Part 1: Supported and unsupported monolithic and multiple glazing

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	6
5	Principle	8
6	Required characteristics of glass products	10
6.1	Appropriate glass products	10
6.2	Dimensional tolerances	11
6.3	Glass shapes	12
6.4	Corners, notches and holes	12
7	Verification of the suitability of glass products for use in SSG systems when exposed to ultra-violet (UV) radiation	13
7.1	General	13
7.2	Insulating glass unit (IGU)	13
7.3	Laminated glass or monolithic glass -- Situation 3 (see Figure 3)	15
7.4	Assessment of the adhesion between the sealant and the glass	15
8	Design	16
8.1	Calculation of the thickness of the glass	16
8.2	Calculation of the height of the outer sealant of the IGU for supported and unsupported glazing	16
8.3	Calculation of the height of the outer sealant of the IGU for unsupported glazing	20
	Annex A (informative) Assembly requirement	21
	Annex B (normative) Structural and/or ultra-violet (UV) -resistant sealant (for use with structural sealant glazing and/or IGUs with exposed seals)	26
	Annex C (normative) Evaluation of tests results	42
	Annex D (normative) Shear at 23 °C -- Test method	46
	Annex E (normative) Factory production control (FPC) requirements for sealants	48
	Annex F (normative) Outer seal of an IGU -- Category differentiation	53
	Annex G (normative) Formation of bubbles	56
	Annex H (informative) Sealing, structural bonding and UV resistance schematic illustrations	57
	Annex I (normative) Initial testing of the bonding of sealant to a non-glass substrate	60
	Bibliography	62