

DIN EN 13164:2013-03 (E)

Thermal insulation products for buildings - Factory made extruded polystyrene foam (XPS) products - Specification

Contents		Page
Foreword		5
1	Scope	7
2	Normative references	7
3	Terms, definitions, symbols, units, abbreviated terms	8
4	Requirements	12
4.1	General	12
4.2	For all applications	12
4.2.1	Thermal resistance and thermal conductivity	12
4.2.2	Length, width, squareness, flatness	13
4.2.3	Thickness	13
4.2.4	Reaction to fire of the product as placed on the market	14
4.2.5	Durability characteristics	14
4.3	For specific applications	14
4.3.1	General	14
4.3.2	Dimensional stability under specified conditions	14
4.3.3	Deformation under specified compressive load and temperature conditions	15
4.3.4	Compressive stress or compressive strength	15
4.3.5	Tensile strength perpendicular to faces	16
4.3.6	Compressive creep	16
4.3.7	Water absorption	17
4.3.8	Freeze-thaw resistance	17
4.3.9	Water vapour transmission	18
4.3.10	Release of dangerous substances	18
4.3.11	Reaction to fire of the product in standardized assemblies simulating end-use applications	18
4.3.12	Continuous glowing combustion	19
4.3.13	Shear strength	19
5	Test methods	19
5.1	Sampling	19
5.2	Conditioning	19
5.3	Testing	19
5.3.1	General	19
5.3.2	Thermal resistance and thermal conductivity	19
6	Designation code	21
7	Evaluation of conformity	22
7.1	General	22
7.2	Initial type testing	22
7.3	Factory production control	22
8	Marking and labelling	23
Annex A (normative)	Determination of the declared values of thermal resistance and thermal conductivity	24

A.1	General	24
A.2	Input data	24
A.3	Declared values	24
A.3.1	General	24
A.3.2	Case where thermal resistance and thermal conductivity are declared	24
A.3.3	Case where only thermal resistance is declared	25
Annex B (normative) Initial type testing (ITT) and Factory production control (FPC)		27
Annex C (normative) Determination of the aged values of thermal resistance and thermal conductivity		30
C.1	General	30
C.2	Procedure for XPS foam without diffusion tight facings	30
C.2.1	Principle	30
C.2.2	Sample preparation	30
C.2.3	Procedure	30
C.3	Procedure for XPS foam for use with diffusion tight facing on both sides	31
C.3.1	Principle	31
C.3.2	Ageing procedure	31
C.4	Determination of value after ageing: "aged value"	31
C.4.1	Determination of aged value for XPS products without diffusion tight facings on both sides	31
C.4.2	Determination of aged value for XPS products for use with diffusion tight facing on both sides	32
C.5	Blowing agent	33
C.6	Product grouping	33
Annex D (normative) XPS multi-layered insulation products		34
D.1	General	34
D.2	Requirements	34
D.2.1	For all applications	34
D.2.2	For specific applications	35
D.3	Test methods	35
D.4	Evaluation of conformity	35
Annex E (informative) Additional properties		36
E.1	General	36
E.2	Behaviour under cyclic loading	36
E.3	Compressive modulus of elasticity	36
E.4	Bending strength	36
E.5	Determination of volume percentage of closed cells	36
Annex F (informative) Plan for cutting test specimen		38
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive		40
ZA.2 Procedures for attestation of conformity of factory made extruded polystyrene foam products		42
ZA.2.1 Systems of attestation of conformity		42
Bibliography		48
Tables Table 1 -- Tolerances of length, width, squareness and flatness		13
Table 2 -- Classes for thickness tolerances		13
Table 3 -- Dimensional stability under specified conditions		15

Table 4 -- Levels for deformation under specified compressive load and temperature conditions	15
Table 5 -- Levels for compressive stress or compressive strength	16
Table 6 -- Levels for tensile strength, perpendicular to faces	16
Table 7 -- Levels for long term water absorption by total immersion	17
Table 8 -- Levels for long term water absorption by diffusion	17
Table 9 -- Test methods, test specimens and conditions	20
Table A.1 -- Values for k for one sided 90 % tolerance interval with a confidence level of 90 %	25
Table B.1 -- Minimum number of tests for ITT and minimum product testing frequencies	27
Table B.2 -- Minimum product testing frequencies for the reaction to fire characteristics	29
Table E.1 -- Test methods, test specimens, conditions and minimum testing frequencies	37
Table ZA.1 -- Relevant clauses for extruded polystyrene foam products	41
Table ZA.2 -- Systems of attestation of conformity	42
Table ZA.3.1 -- Assignment of evaluation of conformity tasks for products under system 1 for reaction to fire and system 3 for other characteristics	43
Table ZA.3.2 -- Assignment of evaluation of conformity tasks for products under system 3 or system 3 combined with system 4 for reaction to fire	44
Figures Figure ZA.1 -- Example CE marking information	47