DIN EN 1793-6:2013-04 (E)

Road traffic noise reducing devices - Test method for determining t he acoustic performance - Part 6: Intrinsic characteristics - In-situ values of airborne sound insulation under direct sound field conditions

Contents

Page

Foreword 3

Introduction 4

1 Scope 7

2 Normative references 7

3 Terms and definitions 7

4 Sound insulation index measurements 12
4.1 General principle 12
4.2 Measured quantity 12
4.3 Test arrangement 12
4.4 Measuring equipment 18
4.4.1 Components of the measuring system 18
4.4.2 Sound source 18
4.4.3 Test signal 18
4.5 Data processing 19
4.5.1 Calibration 19
4.5.2 Sample rate 19
4.5.3 Background noise 19
4.5.4 Scanning technique using a single microphone 19
4.5.5 Scanning technique using nine microphones 20
4.5.6 Adrienne temporal window 21
4.5.7 Placement of the Adrienne temporal window 22
4.5.8 Low frequency limit and sample size 23
4.6 Positioning of the measuring equipment 24
4.6.1 Selection of the measurement positions 24
4.6.2 Post measurements 25
4.6.3 Additional measurements 25
4.6.4 Reflecting objects 25
4.6.5 Safety considerations 25
4.7 Sample surface and meteorological conditions 25
4.7.1 Condition of the sample surface 25
4.7.2 Wind 25
4.7.3 Air temperature 25
4.8 Single-number rating 26
4.8.1 General 26
4.8.2 Acoustic elements 26
4.8.3 Posts 26
4.8.4 Global 27

5 Measurement uncertainty 27

6 Measuring procedure 27

7 Test report 28

Annex A (normative) Categorisation of single-number rating 30

Annex B (informative) Guidance note on use of the single-number rating 31

Annex C (informative) Measurement uncertainty 32

Annex D (informative) Template of test report on airborne sound insulation of road traffic noise reducing devices 35

Bibliography 47