

DIN EN 13163:2013-03 (E)

Thermal insulation products for buildings - Factory made expanded polystyrene (EPS) products - Specification

| Contents | | Page |
|---|---|-------------|
| Foreword | | 5 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms, definitions, symbols, units and abbreviated terms | 9 |
| 3.1 | Terms and definitions | 9 |
| 3.2 | Symbols, units and abbreviated terms | 10 |
| 4 | Requirements | 13 |
| 4.1 | General | 13 |
| 4.2 | For all applications | 13 |
| 4.3 | For specific applications | 16 |
| 5 | Test methods | 22 |
| 5.1 | Sampling | 22 |
| 5.2 | Conditioning | 22 |
| 5.3 | Testing | 23 |
| 6 | Designation code | 26 |
| 7 | Evaluation of conformity | 27 |
| 7.1 | General | 27 |
| 7.2 | Initial type testing | 27 |
| 7.3 | Factory production control | 27 |
| 8 | Marking and labelling | 27 |
| Annex A (normative) | | 29 |
| A.1 | General | 29 |
| A.2 | Input data | 29 |
| A.3 | Declared values | 29 |
| Annex B | | 31 |
| B.1 | Initial type testing and factory production control | 31 |
| B.2 | Indirect testing for factory production control | 36 |
| Annex C | | 38 |
| Annex D (normative) Multi layered EPS products | | 39 |
| D.1 | General | 39 |
| D.2 | Requirements | 39 |
| D.3 | Test methods | 40 |
| D.4 | Evaluation of conformity | 40 |
| Annex E (informative) Verification of the reaction to fire classification of raw materials | | 41 |

| | | |
|---|---|----|
| E.1 | General | 41 |
| E.2 | Material covered by this annex | 41 |
| E.3 | Preparation of samples | 41 |
| E.4 | Initial type tests for EPS raw material | 41 |
| E.5 | Factory Production Control for EPS raw material | 42 |
| E.6 | Certification of conformity for EPS raw material | 42 |
| E.7 | Continuous surveillance of EPS raw material | 43 |
| E.8 | Material certificate for EPS raw material | 43 |
| E.9 | Requirement for raw material supply | 44 |
| Annex F (informative) Additional properties | | 45 |
| F.1 | General | 45 |
| F.2 | Long-term compressive behaviour | 45 |
| F.3 | Shear behaviour | 45 |
| F.4 | Water vapour diffusion resistance factor | 46 |
| F.5 | Examples of determination of thermal conductivity | 46 |
| F.6 | Additional information | 47 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products directive | | 48 |
| Bibliography | | 56 |
| Tables Table 1 -- Classes of dimensional tolerances | | 15 |
| Table 2 -- Dimensional stability under specified temperature or specified temperature and humidity conditions | | 16 |
| Table 3 -- Levels for compressive stress at 10 % deformation | | 17 |
| Table 4 -- Levels for bending strength | | 17 |
| Table 5 -- Levels of deformation under specified compressive load and temperature conditions | | 18 |
| Table 6 -- Levels for dynamic stiffness | | 20 |
| Table 7 -- Classes for thickness tolerances | | 21 |
| Table 8 -- Levels for compressibility | | 21 |
| Table A.1 -- Values for k for one sided 90 % tolerance interval with a confidence level of 90 % | | 30 |
| Table B.1 -- Number of tests for ITT and minimum product testing frequencies | | 31 |
| Table B.2 -- Minimum product testing frequencies for the reaction to fire characteristics | | 34 |
| Table C.1 -- Classification of EPS products | | 38 |
| Table C.2 -- Classification EPS products with acoustical properties | | 38 |
| Table E.1 -- Testing frequency of raw material | | 43 |
| Table F.1 -- Correlation between bending strength and shear strength | | 45 |
| Table F.2 -- Tabulated values of water vapour diffusion resistance index and water vapour permeability | | 46 |
| Table ZA.1 -- Relevant clauses for EPS and intended uses | | 49 |
| Table ZA.2 -- Systems of attestation of conformity | | 50 |

Table ZA.3.1 -- Assignment of evaluation of conformity tasks for products under system 1 for reaction to fire and system 3 for other characteristics51

Table ZA.3.2 - Assignment of evaluation of conformity tasks for products under system 3 or 3 combined with system 4 for reaction to fire52

Figures Figure F.1 -- Example of a relationship between thermal conductivity (at 50 mm reference thickness and 10 °C mean temperature) apparent density for indirect testing of non infrared absorbing EPS47

Figure ZA.1 -- Example CE marking information55