DIN EN 14315-2:2013-04 (E)

Thermal insulating products f or buildings - In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products - Part 2: Specification for the installed insulation products

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms, definitions, symbols and abbreviations 4
3.1 Terms and definitions 4
3.2 Symbols and abbreviations 6

4 Requirements 6
4.1 General 6
4.2 Suitability of the building for the installation of the product 6

5 In-situ measurements and calculations 6
5.1 Declared installed insulation thickness 6
5.2 Declared installed aged thermal resistance, RD 6
5.3 Declared installed insulation density 6
5.4 Foam quality checks carried out by the installer 7

6 Guidelines for installation 7

7 Installer's declaration 7

Annex A (normative) Method of the determination of the declared installed insulation thickness 8

Procedure 8

Annex B (normative) Methods for the determination of the declared installed insulation density 9

B.1 Principle 9
B.2 Procedure 9
B.2.1 General 9
B.2.2 Destructive testing 9
B.2.3 Non-destructive testing 9
B.3 Test report 9

Annex C (normative) Immersion method for the determination of the declared installed insulation density 10

C.1 Scope 10
C.2 Principles 10
C.3 Necessary equipment 10
C.4 Products and reagents 10
C.5 Procedure 10
C.6 Results 11

Annex D (normative) Suitability of the building to receive the insulation product 12

D.1 Building 12
D.2 Site survey 12

Annex E (normative) Installation guidelines 13

E.1 General 13
E.2 Substrate preparation 13
E.3 Substrate conditions 13
E.4 Spraying machine preparation 13
E.4.1 Preparation 13
E.4.2 Mixing ratio 13
E.5 Spraying procedure 14
E.6 Protection against UV radiation 14
E.7 An example of a suitable declaration form which can be used by the installer 15

Bibliography 16