

# DIN EN 572-2:2012-11 (E)

## Glass in building - Basic soda lime silicate glass products - Part 2: Float glass

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>4</b>
<b>4</b>	<b>Dimensional requirements .....</b>	<b>5</b>
<b>4.1</b>	<b>Thickness .....</b>	<b>5</b>
<b>4.1.1</b>	<b>General .....</b>	<b>5</b>
<b>4.1.2</b>	<b>Tolerances .....</b>	<b>6</b>
<b>4.2</b>	<b>Length, width and squareness .....</b>	<b>6</b>
<b>5</b>	<b>Quality requirements .....</b>	<b>7</b>
<b>5.1</b>	<b>General .....</b>	<b>7</b>
<b>5.2</b>	<b>Methods of observation and measurement .....</b>	<b>7</b>
<b>5.2.1</b>	<b>Optical faults .....</b>	<b>7</b>
<b>5.2.2</b>	<b>Visual faults .....</b>	<b>8</b>
<b>5.3</b>	<b>Acceptance levels .....</b>	<b>9</b>
<b>5.3.1</b>	<b>Optical faults .....</b>	<b>9</b>
<b>5.3.2</b>	<b>Spot faults .....</b>	<b>9</b>
<b>6</b>	<b>Designation .....</b>	<b>10</b>
<b>Annex A (normative) Method for measuring spot fault size (including halo) .....</b>		<b>11</b>
<b>A.1</b>	<b>Conditions of observation .....</b>	<b>11</b>
<b>A.2</b>	<b>Measurement of the size of the spot fault including the halo .....</b>	<b>12</b>
<b>Bibliography .....</b>		<b>14</b>