

DIN EN 572-7:2012-11 (E)

Glass in building - Basic soda lime silicate glass products - Part 7: Wired or unwired channel shaped glass

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Dimensional requirements | 6 |
| 4.1 | Method of measurement | 6 |
| 4.1.1 | Width, B, and height of flange, d | 6 |
| 4.1.2 | Length, H | 6 |
| 4.1.3 | Thickness, c | 6 |
| 4.1.4 | Flange deviation | 6 |
| 4.1.5 | Squareness of cut | 7 |
| 4.1.6 | Wire inlay | 7 |
| 4.2 | Tolerances | 7 |
| 4.2.1 | Width, B, height of flange, d, and thickness c | 7 |
| 4.2.2 | Length | 7 |
| 4.2.3 | Flange deviation | 7 |
| 4.2.4 | Squareness of cut | 7 |
| 4.2.5 | Wire inlay | 7 |
| 5 | Quality requirements | 8 |
| 5.1 | General | 8 |
| 5.2 | Methods of observation and measurement | 8 |
| 5.2.1 | Visual faults | 8 |
| 5.2.2 | Wire faults | 8 |
| 5.3 | Acceptance levels | 9 |
| 5.3.1 | Visual faults | 9 |
| 5.3.2 | Wire faults | 9 |
| 6 | Designation | 9 |
| Bibliography | | 10 |