DIN EN 14318-2:2013-04 (E)

Thermal insulating products for buildings - In-situ formed dispensed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products - Part 2: Specification for the installed insulation products

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms, definitions, symbols and abbreviations 4
3.1 Terms and definitions 4
3.2 Symbols and abbreviations 5

4 Requirements 6
4.1 General 6
4.2 Suitability of the building for the installation of the product 6

5 In-situ measurements and calculations 6
5.1 Declared installed insulation thickness: Average cavity width 6
5.2 Declared installed aged thermal resistance, RD 6
5.3 Foam quality checks carried out by the installer 6

6 Guidelines for installation 6

7 Installer's declaration 7

Annex A (normative) Method for the determination of the declared installed insulation thickness: Average cavity width 8

A.1 Procedure 8
A.2 Calculation 8

Annex B (normative) Suitability of the building to receive the insulation product 9

B.1 Building 9
B.2 Site survey 9

Annex C (normative) Control of the passage of water vapour in insulated masonry cavities 11

Annex D (normative) Installation guidelines 12

D.1 General 12
D.2 Suitability of cavity 12
D.3 Dispensing machine preparation 12
D.3.1 Preparation 12
D.3.2 Mixing ratio 12
D.4 Dispensing procedure 12

Bibliography 13