

DIN EN 14318-2:2013-04 (E)

Thermal insulating products for buildings - In-situ formed dispensed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products - Part 2: Specification for the installed insulation products

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms, definitions, symbols and abbreviations	4
3.1	Terms and definitions	4
3.2	Symbols and abbreviations	5
4	Requirements	6
4.1	General	6
4.2	Suitability of the building for the installation of the product	6
5	In-situ measurements and calculations	6
5.1	Declared installed insulation thickness: Average cavity width	6
5.2	Declared installed aged thermal resistance, RD	6
5.3	Foam quality checks carried out by the installer	6
6	Guidelines for installation	6
7	Installer's declaration	7
Annex A (normative) Method for the determination of the declared installed insulation thickness:		
	Average cavity width	8
A.1	Procedure	8
A.2	Calculation	8
Annex B (normative) Suitability of the building to receive the insulation product		9
B.1	Building	9
B.2	Site survey	9
Annex C (normative) Control of the passage of water vapour in insulated masonry cavities		11
Annex D (normative) Installation guidelines		12
D.1	General	12
D.2	Suitability of cavity	12
D.3	Dispensing machine preparation	12
D.3.1	Preparation	12
D.3.2	Mixing ratio	12
D.4	Dispensing procedure	12
Bibliography		13