

DIN EN 14320-2:2013-04 (E)

Thermal insulating products for building equipment and industrial installations - In-situ formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products - Part 2: Specification for the installed insulation products

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms, definitions, abbreviations and symbols	4
3.1	Terms and definitions	4
3.2	Symbols and abbreviations	6
4	Requirements	6
4.1	General	6
4.2	Suitability of the building equipment or industrial installation for the installation of the product	6
5	In-situ measurements and calculations	6
5.1	Declared installed insulation thickness	6
5.2	Declared installed aged thermal resistance, RD	6
5.3	Declared installed insulation density	7
5.4	Foam quality checks carried out by the installer	7
6	Guidelines for installation	7
7	Installer's declaration	7
Annex A (normative) Method for the determination of the declared installed insulation thickness		8
Annex B (normative) Methods for the determination of the declared installed insulation density		9
B.1	Principle	9
B.2	Procedure	9
B.2.1	General	9
B.2.2	Destructive testing	9
B.2.3	Non-destructive testing	9
B.3	Test report	9
Annex C (normative) Immersion method for the determination of the declared installed insulation density		10
C.1	Scope	10
C.2	Principles	10
C.3	Necessary equipment	10
C.4	Products and reagents	10
C.5	Procedure	10
C.6	Results	11
Annex D (normative) Installation guidelines		12
D.1	General	12

D.2	Substrate preparation	12
D.3	Substrate conditions	12
D.4	Atmospheric conditions	12
D.5	Spraying machine preparation	12
D.5.1	General	12
D.5.2	Mixing ratio	12
D.6	Spraying procedure	13
Annex E (normative)	Suitability of the building equipment or industrial installation to receive the insulation product	14
E.1	Building equipment or industrial installation	14
E.2	Site survey	14
Bibliography		15