

DIN EN ISO 12569:2013-03 (E)

Thermal performance of buildings and materials - Determination of specific airflow rate in buildings - Tracer gas dilution method (ISO 12569:2012)

Contents	Page
Foreword	3
Introduction	4
1 Scope	5
2 Terms and definitions	5
3 Measurement method and its selection	6
3.1 General	6
3.2 Concentration decay method	8
3.3 Continuous dose method	11
3.4 Constant concentration method	13
3.5 Type of tracer gas	14
3.6 Measurement apparatus	15
4 Procedure	17
4.1 Building preparations	17
4.2 Ancillary measurements	17
4.3 Concentration decay method	17
4.4 Continuous dose methods	24
4.5 Constant concentration method	29
5 Accuracy	31
5.1 Tracer gas dose procedure and room concentration distribution	32
5.2 Tracer gas sampling and storage method	32
5.3 Tracer gas concentration measuring instruments	32
5.4 Changes in outside wind and outside air temperature and schedule of air conditioning system	33
6 Test report	33
6.1 General	33
6.2 All details necessary to identify the simulation tested	33
6.3 Details of heating and ventilation systems	33
6.4 Test conditions and apparatus	34
6.5 Collected data and results	34
6.6 Date of the test	34
Annex A (normative) Confidence intervals	35
Annex B (normative) Method to estimate ventilation rate Q_V and effective mixed zone volume V_{emz} simultaneously [3,4]	39
Annex C (informative) Considerations when measuring the ventilation rate of large spaces	43
Annex D (informative) Effects of internal and external temperature difference, temperature change, and outside air concentration change during the measurement period	44
Annex E (informative) Estimation error minimizing method in 2-point and multi-point decay method	48
Annex F (informative) Propagation of error analysis	53
Bibliography	55